

PorousPrep

Air & Water Barrier

R-Guard[®] PorousPrep seals the dry, cut edges of gypsum wall boards exposed in rough openings for windows and doors. The sealed edge makes a perfect surface for easy application of R-Guard[®] Joint & Seam Filler or R-Guard FastFlash[®].

PorousPrep brushes on easily and efficiently, and its glue-like viscosity reduces rundown and potential for spills. PorousPrep usually dries in 30 to 60 minutes when applied to dry surfaces. Use R-Guard[®] PorousPrep as part of a continuous, building-wide air barrier system, or to complement conventional air barrier components.

Advantages

- Ensures application of Joint & Seam Filler or FastFlash[®] to dry cut edges of gypsum wall board is fast and efficient.
- Glue-like viscosity makes application smooth and easy, while reducing potential for spills and rundown.
- Water cleanup.
- No solvent odor.
- Treated surfaces “breathe” – does not trap moisture.

Limitations

- Not for use on wet surfaces.
- Not for use below grade or in locations which are continuously immersed in water.
- Not for use as a structural sealant.

REGULATORY COMPLIANCE

VOC Compliance

R-Guard[®] PorousPrep is compliant with the following national, state and district AIM VOC regulations:

- US Environmental Protection Agency
- California Air Resources Board SCM Districts
- South Coast Air Quality Management District
- Maricopa County, AZ
- Northeast Ozone Transport Commission

Typical Technical Data

FORM	Light blue viscous liquid, mild odor
SPECIFIC GRAVITY	1.02
pH	9.0
WT/GAL	8.49 lbs
ACTIVE CONTENT	16%
TOTAL SOLIDS	16% ASTM D 2369
VOC CONTENT	<100 g/L
FLASH POINT	>212° F (>100° C) ASTM D 3278
FREEZE POINT	32° F (0° C)
SHELF LIFE	2 years in tightly sealed, unopened container

SAFETY INFORMATION

Always read full label and SDS for precautionary instructions before use. Use appropriate safety equipment and job site controls during application and handling.

24-Hour Emergency Information: INFOTRAC at 800-535-5053

PREPARATION

Protect people, vehicles, property, plants, painted surfaces and all non-masonry surfaces from product, residue, splash, fumes and wind drift. Use polyethylene or other proven protective material.

To ensure best results, apply to clean, dry surfaces free of contaminants. Chemical residues, surface coatings or films may adversely affect adhesion. Remove dust, dirt and loose particles before application. Call Customer Care at 800- 255-4255, or visit www.prosoco.com for cleaning recommendations.

Surface & Air Temperatures

Surface and ambient temperatures should be 45°F (7°C) and rising and below 100°F (38°C) during application and drying.

Equipment

Apply using a brush or roller.

Storage & Handling

Keep from freezing. Store in a cool, dry place. Keep container tightly closed when not dispensing. Do not alter or mix with other chemicals. Published shelf life assumes upright storage of factory-sealed containers in a dry place. Maintain temperature

of 45–100°F (7–38°C). Do not double stack pallets. Dispose of unused product and container in accordance with local, state and federal regulations.

APPLICATION

Read “Preparation” and the Safety Data Sheet before use.

ALWAYS TEST each type of surface for suitability and desired results before starting overall application. Test with the same equipment, recommended surface preparation and application procedures planned for general application. Let test dry thoroughly before inspection.

Dilution & Mixing

Apply as packaged. Do not dilute or alter, or use for applications other than specified.

Coverage Rates

Coverage varies based on surface texture and porosity. Always test.

- 200–400 square feet per gallon
- 600 linear feet per gallon

Application Instructions

Seal dry gypsum board edges in rough openings with PorousPrep. Apply to dry raw gypsum board edges by brushing on a thin, uniform coat. Do not over apply. Allow to dry tack free before application of Joint & Seam Filler or FastFlash[®].

Cleanup

Clean tools and equipment immediately with soap and water.

Curing and Drying

Protect from rain or freezing for at least 4 hours. Dry time is approximately 30–60 minutes at 72°F and 40% relative humidity. Dry time will vary depending upon temperature and humidity.

BEST PRACTICES

Surfaces should be clean, dry and in good repair before application.

Adjust drying time based on temperature and humidity. Lower temps and higher humidity can increase dry time. Higher temps and lower humidity can decrease dry time.

Schedule application of R-Guard[®] Joint & Seam Filler or FastFlash[®] to edges sealed with PorousPrep within 24 hours, and preferably during the same working day.

PROSOCO R-Guard[®] Joint & Seam Filler, FastFlash[®] and AirDam[®] are recommended for improved performance of R-Guard Cat.

To schedule field technical support, contact your PROSOCO Technical Customer Care toll-free at 800-255-4255. Field visits by PROSOCO personnel are for the purpose of making technical recommendations only. PROSOCO is not responsible for providing job site supervision or quality control. Proper application is the responsibility of the applicator.

WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

PROSOCO, Inc. warrants this product to be free from defects. **Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose.** The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care – technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our web site at www.prosoco.com, for the name of the PROSOCO representative in your area.