



Air & Water Sealing Screw Fastener with Prong Washer

Air Space (1" Min. - 2" Max.)

Barrel Screw Masonry Anchor w/ Thermal Break Clip, Pintle Wire Tie, & Air & Water Sealing Washer

Termination Bar

Owens Corning® FOAMULAR® 250 XPS (5" Max.)

Face Brick

Flashing

Weep Hole Insert @ Max. 24" O.C.

Drip Edge

Mortar Droppings Collection Device

Min. 3/2" 18 Ga. Galvanized Steel Studs @ 24" O.C. Max.

Owens Corning® EcoTouch® FIBERGLAS™ Batt Insulation (Optional) (FS 25 Faced or Unfaced)

5/8" Type X Exterior Gypsum Sheathing

NFPA 285 Compliant Air & Water Barrier

5/8" Type X Gypsum Board

Galvanized Steel Stud Track

Steel Shelf Angle

Enclosure Solutions

Steel Stud Wall System

Opening Head w/ Shelf Angle Cavity Closure

Date: 05-03-16

Dwg. no. ES-SS-03

Vertical Section

NOTE: This drawing is a general reference intended to show common wall system assembly details. Actual details for each product will vary, therefore, details for each project must be reviewed and approved by the Architect of Record. Manufacturers assume no responsibility for final project drawings or field installation.