



Air Space (1" Min. - 2" Max.)

Fastener # 3" Washer

Thermafiber® RainBarrier® 45
Mineral Wool Insulation

Termination Bar

Barrel Screw Masonry Anchor w/
Thermal Break Clip, Pindle Wire Tie, &
RainBarrier® Clip

Flashing

Weep Hole Insert @ Max. 24" O.C.

Drip Edge

Mortar Droppings Collection Device

5/8" Type X Gypsum Board

Min. 3/2" 18 Ga. Galvanized Steel
Studs @ 24" O.C. Max.

Owens Corning® EcoTouch®
FIBERGLAS™ Batt Insulation
(Optional) (FS 25 Faced or
Unfaced)

5/8" Type X Exterior Gypsum
Sheathing

Galvanized Steel Stud Track

2x Wood Blocking (Must be FRTW
in Types I and II Construction)

NFPA 285 Compliant
Air & Water Barrier- Wrap into
Rough Opening and Tie into
Window or Door Assembly Per
Manufacturer's Instructions to
Create Continuous Air & Water
Barrier

Steel Lintel

Enclosure Solutions

Steel Stud Wall System

Opening Head w/ Wood Cavity Closure

Date: 05-03-16

Dwg. no. ES-SS-18

Vertical Section

NOTE: This drawing is a general reference intended to show common wall system assembly details. Actual details for each product will vary, therefore, details for each project must be reviewed and approved by the Architect of Record. Manufacturers assume no responsibility for final project drawings or field installation.