



Rodenhouse, Inc. Grip-Deck® Screw  
with Thermal-Grip® c1 Prong Washer

Face Brick

Air Space (1" Min. - 2" Max.)

PROSOCO R-Guard® Cat-5®  
Air & Water Barrier

Owens Corning® FOAMULAR®  
250 XPS (4" Maximum)

Heckmann Building Products  
Pos-I-Tie® with Thermal-Clip® Pintle  
Wire Tie & Rodenhouse, Inc.  
Thermal-Grip® Brick Tie Washer

5/8" Type X Gypsum Board

Min. 3/2" 18 Ga. Galvanized Steel  
Studs at 24" O.C. Max.

Owens Corning® EcoTouch®  
FIBERGLAS™ Batt Insulation  
(Optional) (FS 25 Faced or  
Unfaced)

5/8" Type X Exterior  
Gypsum Sheathing

**CavityComplete®**  
Steel Stud Wall System

Wall Section

Date: 10-12-16	Dwg. no. CC-SS-01	Vertical Section
----------------	-------------------	------------------

NOTE: This drawing is a general reference intended to show common wall system assembly. Actual details for each product will vary, therefore, details for each project must be reviewed and approved by the Architect of Record. Refer to Manufacturers' Product Literature for product data and installation instructions. Manufacturers assume no responsibility for final project drawings or field installation.