



Rodenhouse, Inc. Grip-Deck® Screw
with Thermal-Grip® c1 Prong Washer

Air Space (1" Min. - 2" Max.)

Heckmann Building Products
Pos-I-Tie® with Thermal-Clip® Pintle
Wire Tie & Rodenhouse, Inc.
Thermal-Grip® Brick Tie Washer

Owens Corning® FOAMULAR®
250 XPS (Max. 5")

Face Brick

Owens Corning® EcoTouch®
FIBERGLAS™ Batt Insulation
(Optional) (FS 25 Faced or
Unfaced)

Min. 3½" 18 Ga. Galvanized Steel
Studs @ 24" O.C. Max.

PROSOCO R-Guard® Cat-5®
Air & Water Barrier

5/8" Type X Exterior Gypsum
Sheathing

5/8" Type X Gypsum Board

PROSOCO R-Guard® AirDam®
Sealant Tied into Window or Door
Assembly to Create Continuous
Air & Water Barrier

PROSOCO R-Guard® FastFlash®
Wrapped into Rough Opening

CavityComplete®
Steel Stud Wall System

Opening Jamb w/ Masonry Return Cavity
Closure

Date: 10-12-16

Dwg. no. CC-SS-06

Horizontal Section

NOTE: This drawing is a general reference intended to show common wall system assembly. Actual details for each product will vary, therefore, details for each project must be reviewed and approved by the Architect of Record. Refer to Manufacturers' Product Literature for product data and installation instructions. Manufacturers assume no responsibility for final project drawings or field installation.