



PROSOCO R-Guard® FastFlash®

Mortar Net Solutions™ WeepVent™  
@ Max. 24" O.C.

Heckmann Building Products  
Pos-I-Tie® with ThermaClip® Pintle  
Wire Tie & Rodenhouse, Inc.  
Thermal-Grip® Brick Tie Washer

Rodenhouse, Inc. Grip-Deck® Screw  
with Thermal-Grip® c1 Prong Washer

Face Brick

Air Space (1" Min. - 2" Max.)

PROSOCO R-Guard® Cat-5®  
Air & Water Barrier

Owens Corning® Foamular® 250 XPS  
(4" Maximum)

Roofing Air & Water Membrane to  
Wall Air & Water Membrane

Min. 2X Wood Studs @ 24" O.C.  
Max.

OSB, Plywood, or Gypsum  
Sheathing

Owens Corning® EcoTouch®  
FIBERGLAS™ Batt Insulation  
(Optional) (FS 25 Faced or  
Unfaced)

5/8" Type X Gypsum Board



Wall to Parapet/Roof Transition

Date: 10-12-16

Dwg. no. CC-WS-06

Vertical Section

NOTE: This drawing is a general reference intended to show common wall system assembly. Actual details for each product will vary, therefore, details for each project must be reviewed and approved by the Architect of Record. Refer to Manufacturers' Product Literature for product data and installation instructions. Manufacturers assume no responsibility for final project drawings or field installation.