



WeatherLock® Flex

Flexible Self-Sealing Ice & Water Barrier



FEATURES AND PRODUCT BENEFITS

Protection

WeatherLock Flex Self-Sealing Ice and Water Barrier provides excellent protection against water infiltration resulting from freeze/thaw cycles, wind driven rains and normal water flow around eaves, valleys, vents, chimneys, and skylights.

High Performance

WeatherLock Flex self-sealing ice and water barrier has a flexible and pliable poly surface combined with modified asphalt to conform around irregular shapes, inside corners, and at sharp angles.



▪ Aggressive Self-Adhesive

WeatherLock Flex self-sealing ice and water barrier exceeds the adhesion performance requirements standard to help prevent water migration that could cause interior building damage.

▪ Seals Tight Around Nails

When the top shingles are applied, the WeatherLock Flex self-sealing ice and water barrier will seal around the nail penetration creating a water tight construction.

Easy Application

WeatherLock® Flex self-sealing ice and water barrier was designed to increase ease of installation while maintaining peak performance.

- **Cold Temperature Application**

The flexible and pliable poly surface is designed to perform effectively even in cold weather applications and will not crack when the structure naturally expands and contracts.



- **Slip Resistant Surface**

The raised printed surface of WeatherLock Flex self-sealing ice and water barrier enables excellent traction and safer installation. Compared to the leading brand, WeatherLock Flex self-sealing ice and water barrier exceeds performance expectations.

- **Contractor Convenience**

WeatherLock Flex self-sealing ice and water barrier can be exposed to UV for up to 30 days. Plus, it can be applied over existing poly surface ice and water barriers so re-roofing is easy and less costly.



- **Lays flat**

The construction of WeatherLock Flex self-sealing ice and water barrier allows the product to lay flat during installation with no special treatment required at overlaps. This helps promote a more uniform application of shingles with less rework.

PRODUCT SPECIFICATIONS

SPECIFICATIONS	
Roll Size	3 feet x 75 feet
Coverage	225 square feet
Nominal Roll Weight	59 pounds

APPLICABLE STANDARDS AND CODES

ASTM D1970
ASTM E108/UL 790 (Class A Fire Resistance)
CCMC 13403-R
ICC-ESR 1783

LIMITED WARRANTY

Up to 30 years of coverage when installed with Owens Corning™ roofing shingles. See actual warranty for more details.

SHIPPING

SPECIFICATIONS	
Rolls per pallet	20 rolls
Pallets per truckload	33 pallets (660 rolls)
SAP Short Code	WLFL

AVAILABILITY BY PLANT

Brookville, Compton, Denver, Kearny, Medina, Minneapolis and Summit.

SERVICE GUIDELINES

WeatherLock Flex self-sealing ice and water barrier can be top loaded on any roofing truck in full pallet quantities from 1-10 pallets. For quantities greater than 10 pallets, full truckloads will ship direct from the manufacturing facility.

STOPOVER CRITERIA

Max of 1 stop and final. Max of 200 mile radius between stops.



OWENS CORNING ROOFING AND ASPHALT, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OHIO, USA 43659

1-800-GET-PINK®
www.owenscorning.com/roofing

Pub. No. 10010730-B. Printed in U.S.A. May 2014. THE PINK PANTHER™ & ©1964-2014 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The color PINK is a registered trademark of Owens Corning. ©2014 Owens Corning. All Rights Reserved.

(Brookville, Compton, Denver, Kearny, Medina, Minneapolis and Summit.)