



This home has been professionally insulated with

Owens Corning® PROPINK® L77 Loosefill Insulation

(Job Site Address)

Name _____

Address _____

City _____ State _____ Zip _____

Owens Corning® PROPINK® L77 Loosefill Insulation

Owens Corning will accept no responsibility when the product is not installed in accordance with the product label. Stated R-value is provided by installing the required number of bags at a thickness not less than the labeled minimum thickness. Installation of the required number of bags may yield more than the specified minimum thickness. Failure by the installer to provide both the required bags and at least the minimum thickness will result in lower insulation R-value.

Specification for Open Blow Attics

New Construction

Retrofit

Number of bags used

Estimated R-value of previous insulation

Area of coverage (sq. ft.)

Other type(s) of insulation in attic

Thickness of insulation

Depth of previous insulation

Coverage charts are based on a nominal net bag weight of 32 lbs.

Attics

R-value	Minimum Initial Installed Thickness (Inches)	Minimum Settled Thickness (Inches)	Maximum Coverage Per Bag (sq. ft.)	Minimum Bags Per 1,000 sq. ft.	Minimum Weight (lbs per sq. ft.)
13	4.75	4.75	184.6	5.4	0.173
19	7.00	7.00	125.0	8.0	0.256
22	8.00	8.00	106.3	9.4	0.301
26	9.25	9.25	89.6	11.2	0.357
30	10.50	10.50	77.0	13.0	0.416
38	13.25	13.25	59.9	16.7	0.534
44	15.00	15.00	50.7	19.7	0.631
49	16.75	16.75	45.0	22.2	0.711
60	20.00	20.00	35.8	28.0	0.895

Walls

R-value	Framing	Installed Thickness (inches)	Installed Density (lbs per cu. ft.)	Maximum Coverage per Bag (sq. ft.)	Minimum Bags Per 1,000 sq. ft.	Minimum Weight (lbs per sq. ft.)
14	2x4	3.5	1.25	87.8	11.4	0.364
15	2x4	3.5	1.45	75.7	13.2	0.423
16	2x4	3.5	2.20	49.9	20.1	0.642
22	2x6	5.5	1.25	55.9	17.9	0.573
23	2x6	5.5	1.35	51.7	19.3	0.619
24	2x6	5.5	1.75	40.0	25.0	0.802

Floors

R-value	Framing	Minimum Thickness (inches)	Installed Density (lbs per cu. ft.)	Maximum Coverage Per Bag (sq. ft.)	Minimum Bags Per 1,000 sq. ft.	Minimum Weight (lbs per sq. ft.)
30	2x8	7.25	1.35	39.2	25.5	0.816
38	2x10	9.25	1.35	30.8	32.2	1.041
46	2x12	11.25	1.35	25.3	39.6	1.266

Cathedral Ceiling

R-value	Framing	Minimum Thickness (inches)	Installed Density (lbs per cu. ft.)	Maximum Coverage Per Bag (sq. ft.)	Minimum Bags Per 1,000 sq. ft.	Minimum Weight (lbs per sq. ft.)
30	2x8	7.25	1.35	39.2	25.5	0.816
38	2x10	9.25	1.35	30.8	32.5	1.041
49	2x12	11.25	1.85	18.5	54.2	1.734

Loosefill insulations vary in thermal performance due to factors such as aging, mean temperature, settlement, convection, moisture absorption and installation variation. Convection in glass loosefill insulation installed in open attics can reduce its thermal performance in extreme winter temperatures during the heating season.

Contractor _____ Date _____ Builder _____ Date _____

Company _____ (Signature) _____ Company _____ (Signature) _____

Address _____ Address _____

Phone _____ Phone _____



OWENS CORNING INSULATING SYSTEMS, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OHIO, USA 43659
1-800-GET-PINK®
www.owenscorning.com

Pub. No. 10012954-B. Printed in U.S.A. October 2016. The color PINK is a registered trademark of Owens Corning. © 2016 Owens Corning Insulating Systems, LLC. All Rights Reserved.