



OC HILIGHT[®] MULTI-END ROVING

Unmatched clarity for translucent panels



OC HiLight[®] multi-end roving represents a compelling solution for panels where excellent translucency performance is required.

- ✔ Produced with patented Advantex[®] corrosion resistant E-CR glass by Owens Corning.
- ✔ Compatible with unsaturated polyester resins.
- ✔ Based on process and resin system, OC HiLight[®] roving can be used as an alternative to OC Paneluxe[®] roving.

Product Benefits



Excellent Processability

- Designed for excellent processing at various line speeds, OC HiLight[®] roving features easy unwinding and chopping, flat lay-down, and uniform dispersion with low fuzz and static.
- With high impregnation and wet-through characteristics, the product allows excellent resin flow in translucent applications.



Impressive Aesthetics

- Excellent fiber distribution provides a homogeneous surface aspect with limited fiber prints, resulting in consistent thickness throughout the laminate.
- Absence of white fibers and fiber spring-back along with significant reduction of air entrapment ensures excellent translucency of laminates.



Enhanced Service Life

- Advantex[®] glass helps fight corrosion, enhancing service life compared to standard E-glass.

Application

OC HiLight[®] roving is designed to provide optimal translucency in skylight panels, greenhouses, decorative panels for commercial buildings, and roofs for trucks and industrial buildings.



Technical Characteristics

LINEAR WEIGHT OF ROVING (TEX)	YIELDS (YD/LB)	LOSS ON IGNITION (%) ISO 1887:1995
2400	207	0.65
4800	103	0.65

Availability & Packaging

Each pallet can be packaged in bulk or Creel-Pak™ packaging format. Pallets are stretch-wrapped for load stability and for protection during transport. All individual packages are wrapped with Tack-Pak® packaging to aid package run-out and transfer. More information is available in the Customer Acceptance Standards.

MANUFACTURING REGION	PRODUCT	LAYERS PER PALLET	DOFFS PER LAYER	NUMBER OF ENDS	PALLET NET WEIGHT (KG/LB)
North America	OC HiLight® 2400/4800 tex	3	16	16	820/1,808

Labeling

Each doff has a self-adhesive identification label showing the product description, net weight and production date. Each pallet has at least two identification labels detailing the product reference, pallet net and gross weights, production date and pallet production code.

Storage

Unless otherwise specified, it is recommended to store glass fiber products in a cool, dry area. Ideal conditions are at a temperature between 10 °C and 35 °C and a relative humidity between 35% and 85%. The glass fiber products must remain in their original packaging material until the point of usage. If the storage temperature is below 15 °C, it is recommended that the product be stored in the workshop, within its original packaging, at least 24 hours prior to use to help prevent condensation. The packaging is not waterproof. Be sure to protect the product from the weather and other sources of water. When stored properly, there is no known shelf life to the product, and retesting is advised after three years from the initial production date to ensure optimum performance.

**MAKE
MORE
POSSIBLE™**

Americas
One Owens Corning Parkway
Toledo, Ohio, USA 43659
1-800-GET-PINK™

This information and data contained herein is offered solely as a guide in the selection of product. We believe this information to be reliable but do not guarantee its applicability to the user's process or assume any responsibility or liability arising out of its use or performance. The user agrees to be responsible for thoroughly testing any application of the product to determine its suitability. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose. Statements in this publication shall not be construed as representations or warranties or as inducements to infringe on any patent or violate any law, safety code, or insurance regulation. We reserve the right to modify this document without prior notice.

Pub. No. 10013904-A. OC HiLight® Product Data Sheet. December 2025. English. © 2026 Owens Corning. All Rights Reserved.