



VentSure[®] InFlow[®] Vent

Versatile intake ventilation for asphalt roofs.

As a roofing contractor, you know the value of proper ventilation. The VentSure[®] InFlow[®] Vent is designed to work as an integral part of a VentSure[®] Balanced Air Ventilation System to help protect your roofing jobs. Installation is fast and easy without the need to disturb the soffit, gutter, or fascia. And its versatile design makes it an excellent solution for soffit-less, exposed-rafter homes, or homes without adequate air intake.

- Patent-pending design with bottom intake helps protect against wind-driven rain
- Reduces the potential for ice damming
- 4-foot strip with NFVA of 10 sq. in./lf. complements VentSure[®] 4-Foot Strip Ridge Vent
- Roof-deck application for easy installation
- At-eave or lower-roof installation for primary or supplemental intake





- Durable construction for long-lasting performance
- Easy installation with shiplap ends and alignment notch
- Low-profile, 3-plane design creates a smooth roofline transition

Versatile design for soffit-less, exposed-rafter and traditional roofs.

The VentSure® InFlow® Vent is an intake vent that works with asphalt-shingled roofs. On homes with soffits, it can supplement or replace under-eave vents. On soffit-less homes, its roof deck application makes it an excellent solution. And for homes with an exposed-rafter design, the VentSure® InFlow® Vent can be installed on the lower roof, drawing air through the top of the vent.

Protection against wind-driven rain.

The VentSure® InFlow® Vent uses a patent-pending design to draw air from below. The bottom-intake design helps protect against wind-driven rain up to 110 MPH and creates a smooth, visual profile.

Helps maintain optimal attic conditions.

The VentSure® InFlow® Vent is a key component of a VentSure® Balanced Air Ventilation System. By providing a source of cooler air into the attic, it helps reduce heat and moisture buildup and the occurrence of ice damming, which can lead to premature roof deterioration.

Product Attributes

Warranty Length
20-Year Limited*

Applicable Standards and Codes

ICC-ES AC132—Acceptance Criteria for Attic Vents

FBC-TAS 100(a)-95—Test Procedure for Wind and Wind-Driven Rain Resistance

Florida Product Approval (Pending)

TDI RV-82 listed for usage in Texas Coastal Region

VentSure® InFlow® Vent Product Specifications

Net Free Vent Area	10 sq. in. per lineal ft.
Width	15"
Length	48"
Height	1"
Allowable Roof Pitch	4:12 to 16:12

Shipping Specifications and Short Codes

Product Name	4-Foot Strip InFlow® Vent
Color	Black
Material Code	669651
Short Code	VIN4NF
PC/Carton	10
Cartons/PL	6

* See actual warranty for details, limitations and requirements.

^ Excludes non-Owens Corning™ roofing products such as flashing, fasteners and wood decking.



OWENS CORNING
ROOFING AND ASPHALT, LLC
 ONE OWENS CORNING PARKWAY
 TOLEDO, OHIO, USA 43659
 1-800-GET-PINK®
 www.owenscorning.com

Pub. No. 10017830-A. Printed in U.S.A. December 2013. THE PINK PANTHER™ & ©1964–2013 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The color PINK is a registered trademark of Owens Corning. © 2013 Owens Corning. All Rights Reserved.