



ME1510 MULTI-END ROVING

Higher performance for transportation and beyond

ME1510 multi-end roving represents a compelling solution for structural applications requiring high mechanical properties. This multi-end roving product increases physical properties – enabling vehicle light weighting, increased fuel efficiency and lower CO₂ emissions.

- ✔ Compatible with epoxy and phenolic resins.
- ✔ Produced with patented Advantex® corrosion resistant E-CR glass by Owens Corning.

Product Benefits

- 
Excellent Processing
 - Due to excellent wet-ability in epoxy and phenolic matrices, very high glass content is achievable, enabling excellent processing while compounding.
- 
Outstanding Mechanical Properties
 - Superior strength and flexural modulus enable light weighting in vehicles to increase fuel efficiency, lower CO₂ emissions and increase range in electric vehicles.
- 
Enhanced Service Life
 - Advantex® glass helps fight corrosion, enhancing service life compared to standard E-glass.
- 
Fire Resistant
 - Compatible with phenolic resins used in fire resistance applications such as electric vehicles.
- 
No Odor
 - Epoxy resin system meets low odor requirements in vehicles.

Application

ME1510 is designed to provide optimal performance in Sheet Molding Compound (SMC) applications including: automotive structural parts, electric vehicles, and critical industrial applications that require higher mechanical properties such as oil and gas exploration.

Technical Characteristics

LINEAR WEIGHT OF ROVING	LOSS ON IGNITION (%) ISO 1887:1995	MOISTURE CONTENT (%) ISO 3344:1997
2400 and 4800 TEX 207 and 103 Yield	0.7	≤ 0.10

Availability

Each pallet can be packaged in bulk or Creel-Pak™ packaging format. Pallets are stretch-wrapped for load stability and for protection during transport. All individual packages are wrapped with Tack-Pak™ packaging to aid package run-out and transfer. More information is available in the Customer Acceptance Standards.

PRODUCT	DOFF CHARACTERISTICS			
	DIAMETER (mm)		HEIGHT (mm)	NOMINAL WEIGHT (kg)
	Internal	External		
ME1510 2400 and 4800 TEX	46	285 to 290	254	20.5

Packaging & Labeling

Each bobbin is protected by a plastic film (Tack-Pak®). Please do not remove film during use. Creel-Pak® packaging is available upon request.

Each bobbin has a self-adhesive identification label, showing the product reference and the production date. Each pallet has at least one identification label detailing the product reference, pallet net and gross weights, production date and pallet production code.

The packaging system is designed to allow short term stacking of two pallets. When stacking two-high, care should be taken to correctly and smoothly place the top pallet. It is recommended to use a plywood plate between the two pallets in order not to damage the lower pallet.

Storage

Unless otherwise specified, it is recommended to store glass fiber products in a cool, dry area. Ideal conditions are at a temperature between 10 °C and 35 °C and a relative humidity between 35% and 85%. The glass fiber products must remain in their original packaging material until the point of usage. If the storage temperature is below 15 °C, it is recommended that the product be stored in the workshop, within its original packaging, at least 24 hours prior to use to help prevent condensation. The packaging is not waterproof. Be sure to protect the product from the weather and other sources of water. When stored properly, there is no known shelf life to the product, and retesting is advised after three years from the initial production date to ensure optimum performance.

**MAKE
MORE
POSSIBLE™**

Americas

One Owens Corning Parkway
Toledo, Ohio, USA 43659
1-800-GET-PINK™

Europe

166 Chaussée De La Hulpe
B-1170 Brussels, Belgium
+32 3 674 8211

Asia Pacific

40/F, Pudong Kerry Parkside,
115 Fang Dian Road, Pudong,
Shanghai, 201204, China
+86-21-61019666

This information and data contained herein is offered solely as a guide in the selection of product. We believe this information to be reliable but do not guarantee its applicability to the user's process or assume any responsibility or liability arising out of its use or performance. The user agrees to be responsible for thoroughly testing any application of the product to determine its suitability. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose. Statements in this publication shall not be construed as representations or warranties or as inducements to infringe on any patent or violate any law, safety code, or insurance regulation. We reserve the right to modify this document without prior notice.

Pub. No. 10018975. ME1510 Product Data Sheet. December 2025. English. © 2026 Owens Corning. All Rights Reserved.