



PROCAT®
PROFESSIONAL
LOOSEFILL INSULATION SYSTEM

PROCAT® PROFESSIONAL LOOSEFILL INSULATION SYSTEM

This fact sheet contains important details about Owens Corning's ProCat® PINK® FIBERGLAS™ Loosefill Insulation. Read it carefully.

Owens Corning recommends and provides instructions for installing ProCat® Insulation from the outside of exterior sidewalls. You may also install it from the inside, however, it is important to note that drill and fill installation from the inside requires a strong working knowledge of construction and framing principles, texture matching and other variables. Please consult a professional contractor to perform this job if you do not have this expertise.

In order to achieve the stated R-Values, strictly follow Owens Corning's written instructions and recommendations for the operation, maintenance and service of the ProCat® machine.

Stated R-value is provided by installing the required number of bags at a thickness not less than the label minimum thickness. Installation of the required number of bags may yield more than the specified minimum thickness. Failure by the installer to provide both the required number of bags and at least the minimum thickness will result in lower insulation R-value.

Owens Corning does not recommend or approve blending or adding additional materials or adhesives to this product during installation. Owens Corning will accept no responsibility or liability when the product is not installed in accordance with the product label and installation instructions.

OPEN CAVITY (ATTICS)

Nominal bag weight 33.5 lbs.

R-VALUE	BAGS PER 1000 SQ. FT.	MAXIMUM NET COVERAGE - SQ. FT.	MINIMUM WEIGHT/ SQ. FT.	MINIMUM THICKNESS - INCHES	MINIMUM SETTLED THICKNESS - INCHES
13	5.1	198.0	0.169	4.75	4.75
19	7.8	128.7	0.260	7.00	7.00
22	9.0	110.6	0.303	8.00	8.00
26	10.7	93.5	0.358	9.25	9.25
30	12.4	80.6	0.416	10.50	10.50
38	16.4	60.9	0.550	13.25	13.25
44	19.1	52.3	0.641	15.00	15.00
49	21.5	46.4	0.722	16.5	16.5
60	27.1	36.9	0.908	19.75	19.75

CLOSED CAVITY (WALLS)

Nominal bag weight 33.5 lbs.

R-VALUE	BAGS PER 1000 SQ. FT.	MAXIMUM COVERAGE PER BAG IN SQ. FT.	MINIMUM WEIGHT IN LB/SQ. FT.	MINIMUM INITIAL INSTALLED THICKNESS IN INCHES	INSTALLED DENSITY LB PER CUBIC FOOT
14	11.3	88.4	0.379	3.5	1.30
15	17.0	58.9	0.569	3.5	1.95
22	17.8	56.2	0.596	5.5	1.30
23	20.5	48.7	0.688	5.5	1.50
24	30.8	32.5	1.031	5.5	2.25

¹ This product shows negligible settling, with no loss of R-value.

A ProCat™ Machine with 100' of 2.5" hose was used to determine the coverage information. Open attic coverage uses manufacturers pre-set "Attic" settings. Wall coverage uses 50' of 2.5" hose plus the ProCat™ wall installation kit.

* Refer to installation instructions if using dense mode at eaves.

Read This Before You Buy What you should know about R-Values

The chart shows the R-value of this insulation. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy. There are other factors to consider. The amount of insulation you need depends mainly on the climate, the type and size of your home, and your fuel use patterns and family size. To get the marked R-value, it is essential that this insulation be installed properly.

Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein.

OWENS CORNING INSULATING SYSTEMS, LLC
ONE OWENS CORNING PARKWAY TOLEDO, OH 43659 USA
1-800-GET-PINK® | www.owenscorning.com

Pub. No. 10019591-C. Printed in U.S.A. March 2026.
THE PINK PANTHER™ & © 1964–2026 Metro-Goldwyn-Mayer Studios Inc.
All Rights Reserved. The color PINK is a registered trademark of Owens Corning.
© 2026 Owens Corning. All Rights Reserved.