



# LIFEMAT<sup>®</sup> PASTING MAT OPTIMIZES BATTERY PERFORMANCE

LifeMat<sup>®</sup> Pasting Mat is specifically designed to replace paper scrim and increase the performance of lead acid batteries.

- Glass fiber veil bound by a modified, fast, wet-out acid-resistant acrylic resin.
- Produced with patented Advantex corrosion-resistant E-CR glass by Owens Corning.
- Available in a wide range of widths and roll sizes.

## FOR STABLE LIFETIME PERFORMANCE IN BATTERIES

### Product Benefits



**DROP-IN  
SOLUTION**



**CHEMICAL  
RESISTANCE**



**TENSILE  
STRENGTH**



**SUPERIOR CYCLING  
PERFORMANCE**



**HIGH  
PURITY**

### Designed for Lead-Acid Batteries

- Excellent corrosion resistance with very low electrical resistance (<17mΩ/mm<sup>2</sup>).
- Minimal effect on cold cranking due to the low electrical resistance.

### Exceptional Performance

- Re-enforces the positive active mass at the surface while preventing positive active mass shedding.
- Exceptional oxidation resistance provides additional protection throughout the lifetime of the battery.

### Ease of Use

- LifeMat<sup>®</sup> is pasted onto/into the positive active mass where, upon drying/curing, a very strong bond is formed, eliminating the need for pasting paper.
- Easy to cut and compatible with continuous pasting processes.
- Easily applicable in continuous pasting process.

### Cost Optimization

- No investment or modification of the equipment/process is needed.
- Cost optimization through eliminating the need for cellulosic pasting paper.
- Different porosities are available to match individual paste recipe.







### Applications

LifeMat<sup>®</sup> Pasting Mat is manufactured specifically for use in lead-acid batteries. Main applications include enhanced flooded batteries (Stop/Start), SLI applications for cars and trucks, and AGM for industrial and automotive applications.

**Common Technical Characteristics**  
(Nominal Values)

THICKNESS	TENSILE	ELECTRICAL RESISTANCE
< 0.2 mm	> 50N/50 mm	<17mΩ/mm <sup>2</sup>

**ACID RESISTANCE TEST: 8 DAYS IN H<sub>2</sub>SO<sub>4</sub> AT 70°C**

<b>BEFORE TESTING</b>			
<b>AFTER TESTING</b>			
	LifeMat®	Polyester	Micro-glass

**Specific Technical Characteristics**  
(Nominal Values)

ROLL WIDTH	ROLL DIAMETER
43 mm +	75 mm Core ID

**Packaging & Labeling**

Each individual package is labeled with information including product name, producing plant, production date, and a unique ID allowing full traceability.

**Storage**

It is recommended that the material is stored in a cool, dry area in which the temperature does not exceed 35°C and the relative humidity is maintained below 75%. Material should remain in its original packaging until immediately before use. It is advised that stock rotation of the material is exercised. However, if the above conditions are respected, the material is guaranteed against significant deterioration for a period of three years.



**Americas**

**Owens Corning Composite Materials, LLC.**  
One Owens Corning Parkway  
Toledo, OH 43659 USA  
1-800-GET-PINK®

**Europe**

**European Owens Corning Fibreglas Sprl.**  
166 Chaussée de la Hulpe  
B-1170 Brussels  
Belgium  
+32 3 674 8211

**Asia Pacific**

**Owens Corning Shanghai Regional Headquarters**  
40/F, Pudong Kerry Parkside,  
115 Fang Dian Road, Pudong,  
Shanghai, 201204, China  
+86-21-6101 9666

<https://www.owenscorning.com/composites> | [LifeMat@owenscorning.com](mailto:LifeMat@owenscorning.com)

This information and data contained herein is offered solely as a guide in the selection of product. We believe this information to be reliable but do not guarantee its applicability to the user's process or assume any responsibility or liability arising out of its use or performance. The user agrees to be responsible for thoroughly testing any application of the product to determine its suitability. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose. Statements in this publication shall not be construed as representations or warranties or as inducements to infringe on any patent or violate any law, safety code, or insurance regulation. We reserve the right to modify this document without prior notice.

Pub number: 10023062. LifeMat Pasting Mat Product Data Sheet. April 2021. English.  
THE PINK PANTHER™ & © 1964–2021 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. © 2021 Owens Corning. All Rights Reserved.