



TECHNICAL BULLETIN

INSTALLATION OF OWENS CORNING® SELF-ADHERING MEMBRANES OVER FIRE-RESISTANT TREATED PLYWOOD

ISSUED DECEMBER 2024 - SUPERSEDES PREVIOUS BULLETINS

Issue Description:

Fire-Resistant Treated Plywood (FRP) is required on roofs of various commercial and multi-family residential buildings. The surface of FRP products can vary widely, and we have not yet performed adhesion testing to determine that Owens Corning Roofing self-adhered underlayment products adequately adhere to FRP when initially laid during install. Thus, to help ensure installer safety when these products are installed over FRP, we recommend backnailing at 12" on center in the selvage using minimum 12 gage roofing nails. The Limited Product Warranty will remain in effect for our WeatherLock®, Titanium®, and RhinoRoof® self-adhering underlayments if they are installed over FRP. The Limited Lifetime Warranty will remain in effect for these products when included in a Total Protection Roofing System warranty.

Note: This document supersedes any previous Owens Corning Technical Bulletin on this topic.

**Please contact 419-248-6557 for additional information.
Email: gettech@owenscorning.com**

Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein.



OWENS CORNING SCIENCE AND TECHNOLOGY, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OHIO 43659
1-800-GET-PINK®
www.owenscorning.com

Pub. No. 10023713-B. Printed in U.S.A. August 2025. THE PINK PANTHER™ & © 1964-2025 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The color PINK is a registered trademark of Owens Corning. © 2025 Owens Corning. All Rights Reserved.



BOLETÍN TÉCNICO

INSTALACIÓN DE MEMBRANAS AUTOADHESIVAS CORNING® SOBRE CONTRACHAPADO TRATADO RESISTENTE AL FUEGO

PUBLICADO DICIEMBRE 2024 - SUSTITUYE A LOS BOLETINES ANTERIORES

Descripción del problema:

Se requiere madera contrachapada tratada resistente al fuego (FRP) en techos de varios edificios residenciales comerciales y multifamiliares. La superficie de los productos de FRP puede variar ampliamente, y aún no hemos llevado a cabo pruebas de adherencia para determinar si los productos autoadhesivos base de Owens Corning Roofing se adhieren adecuadamente al FRP al ser colocados inicialmente durante la instalación. Por lo tanto, para ayudar a garantizar la seguridad cuando estos productos son instalados sobre FRP, recomendamos clavarlos por la parte posterior a 12 pulgadas al centro en el orillo utilizando clavos de calibre 12 como mínimo. La Garantía Limitada del Producto permanecerá vigente para nuestras bases autoadhesivas WeatherLock®, Titanium® y RhinoRoof® si se instalan sobre FRP. La Garantía de Por Vida del Producto permanecerá vigente para estos productos cuando están incluidos en una garantía del Sistema para techos Total Protection.

Nota: Este documento sustituye a cualquier boletín técnico previo de Owens Corning sobre este tema.

Para obtener más información, llama al teléfono 419-248-6557.
Correo electrónico: gettech@owenscorning.com

Exención de responsabilidad

La información técnica incluida en este documento se brinda sin cargo ni obligación y se proporciona y acepta bajo el exclusivo riesgo del destinatario. Debido a que las condiciones de uso pueden variar y están fuera de nuestro control, Owens Corning no se hace responsable de la exactitud o confiabilidad de los datos asociados con usos particulares de cualquier producto descrito en el presente documento.



OWENS CORNING SCIENCE AND TECHNOLOGY, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OHIO 43659
1-800-GET-PINK®
www.owenscorning.com

Publicación N.º 10023713-B. Impreso en EE. UU. Agosto de 2025. THE PINK PANTHER™ & © 1964-2025 Metro-Goldwyn-Mayer Studios Inc. Todos los derechos reservados. El color PINK es una marca comercial registrada de Owens Corning. © 2025 Owens Corning. Todos los derechos reservados.