



P207 MULTI-END ROVING

Optimize application performance

P207 multi-end roving represents a compelling solution for fabricators that want to save time while realizing optimal performance for continuous process spray-up applications.

- ✓ Produced with patented Advantex® corrosion resistant E-CR glass by Owens Corning.
- ✓ Compatible with polyester and vinyl ester resin systems.

FOR SPRAY-UP IN LARGE AND VERTICAL PARTS

Product Benefits



Excellent Processing

- Low fuzz combined with ease of chopping, and roll out, outstanding compatibility for flat lay down, and uniform dispersion saves time.
- Designed to provide optimal performance for spray-up applications where medium wet-out speed is preferred.
- Superior processing performances achieved with highly filled resin systems.



Exceptional Performance

- Great surface quality, excellent conform-ability, doesn't trap air, and low springback.
- Features Advantex® glass fiber, which combines the electrical (no static) and mechanical properties of traditional E-glass with the acid corrosion resistance of E-CR glass.
- Ease of use and supreme performance on vertical parts and large or complex molds.

Application

P207 roving can be used in a variety of spray-up applications, including boats, truck caps, vehicle body parts, bath tubs, showers, spas, tanks, and applications with large parts, complex molds, or sharp curvatures.

Technical Characteristics

LINEAR WEIGHT OF ROVING (TEX) (G/KM)	LOSS ON IGNITION (%) ISO 1887:1995	MOISTURE CONTENT (%) ISO 3344:1997
2400 +/- 120	1.10% +/- 0.15	≤ 0.15

Availability & Packaging

PRODUCT	DOFF CHARACTERISTICS			NOMINAL WEIGHT (kg)
	DIAMETER (mm)		HEIGHT (mm)	
	INTERNAL	EXTERNAL		
EC 2400	75	280	260	19

- Each P207 doff is protected by a Tack-Pak® polythene film and identified by an individual label; please do not remove film during use.
- Creel-Pak® and customer-specific packaging may be available upon request.

PRODUCT	DOFF Ø (MM)	PALLET DIMENSIONS LxW (CM)	LAYERS PER PALLET	DOFFS PER LAYER	TOTAL NUMBER OF DOFFS	CREEL-PAK®	PALLETS		MANUFACTURING REGION
						NUMBER OF ENDS	APPROX. HEIGHT (CM)	NET WEIGHT* (KG)	
EC 2400	280	114 x 114	3/4	16	48/64	1 - 2 - 4 - 8 - 16	93/119	912/1216	Europe and North America

Test results will vary by Process and Formulation.

Labeling

Each doff has a self-adhesive identification label, showing the product reference and the production date.

Each pallet has five identification labels detailing the product reference, pallet net and gross weights, production date, and pallet production code.

Storage

Unless otherwise specified, it is recommended to store glass fiber products in a cool, dry area. Ideal conditions are at a temperature between 10 °C and 35 °C and a relative humidity between 35% and 85%. The glass fiber products must remain in their original packaging material until the point of usage. If the storage temperature is below 15 °C, it is recommended that the product be stored in the workshop, within its original packaging, at least 24 hours prior to use to help prevent condensation. The packaging is not waterproof. Be sure to protect the product from the weather and other sources of water. When stored properly, there is no known shelf life to the product, and retesting is advised after three years from the initial production date to ensure optimum performance.

**MAKE
MORE
POSSIBLE™**

Americas

One Owens Corning Parkway
Toledo, Ohio, USA 43659
1-800-GET-PINK™

Europe

166 Chaussée De La Hulpe
B-1170 Brussels, Belgium
+32 3 674 8211

This information and data contained herein is offered solely as a guide in the selection of product. We believe this information to be reliable but do not guarantee its applicability to the user's process or assume any responsibility or liability arising out of its use or performance. The user agrees to be responsible for thoroughly testing any application of the product to determine its suitability. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose. Statements in this publication shall not be construed as representations or warranties or as inducements to infringe on any patent or violate any law, safety code, or insurance regulation. We reserve the right to modify this document without prior notice.

Pub. No. 10024127. P207 Product Data Sheet. December 2025. English. © 2026 Owens Corning. All Rights Reserved.