



M723B DESIGNED TO INCREASE PRODUCTIVITY

M723B chopped strand mat represents an ideal solution where the wet and carry process, minimized fiber shedding, rapid air release, and lower resin consumption are desired.

- Produced with Advantex® corrosion-resistant E-CR glass by Owens Corning.
- Made of medium tex multi-chop strands randomly dispersed and bonded together with a highly soluble polyester powder binder.
- Compatible with polyester, vinyl ester, epoxy, and polyurethane resins.

Product Benefits

Easy Handling and Moldability

- Glass bonding designed to minimize fiber shedding, including in the most demanding molding process.

High Process Efficiency

- Exceptional wet tensile strength perfectly fits with the wet and carrying process.
- Fast wetting and quick air release help reduce the labor required to roll out the part.

High Performance

- Optimized product design allows good surface finish and smooth surface behind gelcoat while providing the final part with exceptional tensile and flexural performances.

Enhanced Service Life

- Compared to standard E-glass, Advantex® glass helps with enhanced service life in applications facing corrosion.

Applications

M723B is designed to be used both as gel coat backup and standard laminate reinforcement for most contact molding applications, including truck parts and panels, marine applications, storage containers, and tanks for corrosives.



Availability

M723B is available in South America. Additional weights and widths are available upon request by contacting your Owens Corning representative.

NOMINAL MAT WEIGHT (G/M ²)	NOMINAL MAT WEIGHT (OZ/FT ²)	ROLL WIDTH (CM)	ROLL WIDTH (IN)
300–450	1.0–1.5	140–280	55–110

Packaging & Labeling

Each roll is wound on a 102 mm (4") internal diameter cardboard tube and fully enclosed in Cling-Pak™ wrap. Twelve rolls are positioned vertically (except width 280 – it is placed horizontally) on each pallet, banded with tape and Cling-Pak™ wrapped for stability and protection.

Each roll bears a label detailing the product description, product code, nominal weight, roll width, roll number, and date of manufacture.

ROLL DIAMETER (CM)	ROLL DIAMETER (IN)	ROLLS PER PALLET	PALLET SIZE (CM)	PALLET SIZE (IN)
32	12.59	12	97 x 129	38.18 x 50.78

Storage

Unless otherwise specified, it is recommended to store glass fiber products in a cool, dry area. Ideal conditions are at a temperature between 10°C and 35°C and a relative humidity between 35% and 85%. The glass fiber products must remain in their original packaging material until the point of usage. If the storage temperature is below 15°C, it is recommended that the product be stored in the workshop, within its original packaging, at least 24 hours prior to use to help prevent condensation. The packaging is not waterproof. Be sure to protect the product from the weather and other sources of water. When stored properly, there is no known shelf life to the product, and retesting is advised after three years from the initial production date to ensure optimum performance.

Americas

Owens Corning Composite Materials, LLC.

One Owens Corning Parkway
Toledo, Ohio 43659 USA
1-800-GET-PINK®

Europe

European Owens Corning Fiberglas Sprl.

166 Chaussée de la Hulpe
B-1170 Brussels
Belgium
+32 3 674 8211

Asia Pacific

Owens Corning Shanghai Regional Headquarters

40/F, Pudong Kerry Parkside,
115 Fang Dian Road, Pudong,
Shanghai, 201204, China
+86-21-6101 9666

South America

Owens Corning Fiberglas A.S. Ltda.

Av. Brasil, 2567
Rio Claro/SP, Brazil
13500-600
0800 707 3312

<https://www.owenscorning.com/composites> | Composites@owenscorning.com

This information and data contained herein is offered solely as a guide in the selection of product. We believe this information to be reliable, but we do not guarantee its applicability to the user's process or assume any responsibility or liability arising out of its use or performance. The user agrees to be responsible for thoroughly testing any application of the product to determine its suitability. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose. Statements in this publication shall not be construed as representations or warranties or as inducements to infringe on any patent or violate any law, safety code, or insurance regulation. We reserve the right to modify this document without prior notice.

Pub number: 10024528. M723B_product data sheet. May 2021. English.

© 2021 Owens Corning. All Rights Reserved.