



3050F EFFICIENT AND RELIABLE PERFORMANCE

3050F multi-end roving is specifically designed to provide reliable processing in medium and high-scale gun-roving applications, providing excellent efficiency and performance in the final part.

- Produced with patented Advantex® corrosion-resistant E-CR glass by Owens Corning.
- Sizing designed to provide reliable processing in medium and high-scale spray-up processes.
- Compatible with polyester and vinyl ester resins.

FOR SPRAY-UP APPLICATIONS

Product Benefits

Increased Efficiency

- Low fuzz combined with easy chopping, roll-out, and uniform dispersion saves time.

Excellent Performance

- Good mechanical properties, desirable surface quality, and excellent conformability. Product does not trap air and provides low spring back.

High Process Efficiency

- Designed to provide optimal performance for spray-up applications, providing reliable performance in various types of part complexities.

Enhanced Service Life

- Advantex® glass helps fight corrosion, enhancing service life compared to standard E-glass.

Applications

3050F roving is designed to be used in a variety of spray-up applications, including boats, truck caps, vehicle body parts, bath tubs, showers, spas, tanks, and applications with complex molds or sharp curvatures.



Availability 3050F is available in South America.

LINEAR WEIGHT (TEX)	LINEAR WEIGHT (YIELD)	LOSS ON IGNITION (5) ISO 1887:1995
2400	1473	1.15
4000	2455	1.15

Packaging & Labeling Additional weights and widths are available upon request by contacting your Owens Corning representative. Each 3050F doff is protected by a tack-wrap polythene film and identified by an individual label; please do not remove film during use.

Creel-Pak™ and customer-specific packaging may be available upon request.

PRODUCT	LINEAR WEIGHT (TEX)	DOFF Ø (MM)	PALLET SIZE L X C X A (CM)	LAYERS PER PALLET	BOBBINS PER LAYER	TOTAL NUMBER OF BOBBINS	NET WEIGHT* (KG)
3050F	2400	300–310	129 x 97 x 117	4	12	48	1050
	4000						

Each roll bears a label detailing the product description, product code, nominal weight, and date of manufacture.

Storage It is recommended to store glass fiber products in a cool, dry area. The glass fiber products must remain in their original packaging material until the point of usage; the product should be stored in the workshop, within its original packaging, 48 hours prior to its utilization, to allow it to reach the workshop temperature condition and prevent condensation, especially during the cold season. The packaging is not waterproof. Be sure to protect the product from the weather and other sources of water. When stored properly, there is no known shelf life to the product, but retesting is advised after two years from the initial production date to ensure optimum performance.



Americas

Owens Corning Composite Materials, LLC.
One Owens Corning Parkway
Toledo, Ohio, USA 43659
1-800-GET-PINK®

Europe

European Owens Corning Fiberglas Sprl.
166 Chaussée de la Hulpe
B-1170 Brussels
Belgium
+32 3 674 8211

Asia Pacific

Owens Corning Shanghai Regional Headquarters
40/F, Pudong Kerry Parkside,
115 Fang Dian Road, Pudong,
Shanghai, 201204, China
+86-21-6101 9666

South America

Owens Corning Fiberglas A.S. Ltda.
Av. Brasil, 2567
Rio Claro/SP, Brazil
13500-600
0800 707 3312

<https://www.owenscorning.com/composites> | Composites@owenscorning.com

This information and data contained herein is offered solely as a guide in the selection of product. We believe this information to be reliable but do not guarantee its applicability to the user's process or assume any responsibility or liability arising out of its use or performance. The user agrees to be responsible for thoroughly testing any application of the product to determine its suitability. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose. Statements in this publication shall not be construed as representations or warranties or as inducements to infringe on any patent or violate any law, safety code, or insurance regulation. We reserve the right to modify this document without prior notice.

Pub number: 10024539. 3050F_product data sheet. December 2020. English.

THE PINK PANTHER™ & © 1964–2020 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. © 2020 Owens Corning. All Rights Reserved.