



# PINK NEXT GEN® FIBERGLAS™ FLAME SPREAD 25

## Features

- Excellent thermal control
- Effective acoustical performance
- Provides long-term performance and will not settle or slump within wall cavities
- Less dust than other fiberglass insulation products
- Excellent recovery characteristics
- Compression packaging speeds job site handling and installation
- Facing does not require contact with thermal barrier, can be left exposed

## Standards, Codes Compliance

- Manufactured in compliance with ASTM C665
- PINK Next Gen® Fiberglas™ Flame Spread 25 insulation is accepted for use in all ICC building construction types (I through V)
- Certified to meet California Code of Regulations, Title 24, Chapter 12-13, Article 3, "Standards for Insulating Material"

## Physical Properties

PROPERTY (UNIT)	TEST	VALUE
Thermal Resistance	ASTM C518	See "Availability" table for R-values
Surface Burning Characteristics (flame spread/smoke developed)	ASTM E84 <sup>1</sup>	
FSK		< 25/< 50
Critical Radiant Flux (W/cm <sup>2</sup> )	ASTM E970	>0.12
Water Vapor Permeance (perms)		
FSK	ASTM E96 <sup>2</sup>	0.5
Water Vapor Sorption (by weight)	ASTM C1104/C1104M	< 5%
Odor Emission	ASTM C1304	pass
Corrosion Resistance	ASTM C1617	pass – steel
Fungi Resistance (fiberglass only)	ASTM C1338	pass

1 ASTM E84 is used solely to measure and describe properties of products in response to heat and flame under controlled laboratory conditions, and should not be used to describe or approve the fire hazard of materials under actual fire conditions. However, the results of these tests may be used as elements of a fire risk assessment that takes into account all of the factors of the fire hazard of a particular end use. Values are reported to the nearest five rating.  
2 Dessicant method.

Owens Corning® PINK Next Gen® Fiberglas™ Flame Spread 25 insulation is a preformed, flexible blanket insulation. It is produced in R-values from 11 to 30, at thickness from 3½ to 9½" inches. It is available in FSK (foil-scrim-Kraft), which acts as a vapor retarder and provides a neat, finished appearance.

## Applications

- Wall, floor, and roof/ceiling assemblies where the insulation will be left exposed, or where a low flame spread vapor retarder facing is required
- Concealed applications of assemblies for non-combustible construction
- Metal framed assembly cavities or attached to surfaces with impaling pins

## Design Considerations

- The building thermal barrier (insulation) should be in continual alignment with the building air barrier
- In framed cavities, product thickness should match the depth of the framing members
- Follow the local, applicable building code(s) to determine the need for and placement of a vapor retarder
- Do not install insulation on top, or within 3 inches of a recessed light fixture, unless the fixture is labeled as "insulation contact" (IC) rated

## Availability

APPLICATION	WIDTH	LENGTH	THICKNESS	R-VALUE <sup>3</sup>
Metal Frame Walls				
FSK	16"	96"	3.5"	13
FSK	24"	96"	3.5"	13
FSK	16"	96"	6.5"	19 <sup>4</sup>
FSK	24"	96"	6.5"	19 <sup>4</sup>
FSK	16"	96"	6"	21
Floor/Ceiling				
FSK	16"	48"	9.5"	30
FSK	24"	48"	9.5"	30

3 Tested per ASTM C518.

4 Delivers R17 when installed in a 5.5" deep cavity. Delivers R18 when installed in a 6" deep cavity.

## Installation

See Owens Corning publication "Installation Guide for Light Density Building Insulation" (Pub. No. 10017858) for more information. Both FSK and PSK PINK Next Gen® Fiberglas™ Flame Spread 25 insulation facing options are more abuse-resistant than most other building insulation facings. However, when it is installed in areas where the material may be subject to abuse, suitable protection should be provided.

## Certifications and Sustainable Features

- GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage; for more information, visit [ul.com/gg](http://ul.com/gg)
- Environmental Product Declaration (EPD) has been verified by SCS Global



## Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for, the accuracy or reliability of data associated with particular uses of any product described herein.

SCS Global Services provides independent verification of recycled content in building materials and verifies recycled content claims made by manufacturers. For more information, visit [www.SCSglobalservices.com](http://www.SCSglobalservices.com).

LEED® is a registered trademark of the U.S. Green Building Council.

## Notes

Fiberglass products may cause temporary skin and mucous membrane itching due to the mechanical abrasion effects of fibers, a condition which is completely reversible.

For additional information, refer to the Safe Use Instruction Sheet (SUIS) found in the SDS Database via <http://sds.owenscorning.com>.

**OWENS CORNING INSULATING SYSTEMS, LLC**  
ONE OWENS CORNING PARKWAY  
TOLEDO, OH 43659 USA

**1-800-GET-PINK®**  
**[www.owenscorning.com](http://www.owenscorning.com)**