



PINK NEXT GEN™ FIBERGLAS™ INSULATION

Submittal Sheet

Contractor: _____

Project: _____

Owens Corning® PINK Next Gen™ Fiberglas™ Insulation is flexible, light-density insulation with a variety of facings and uses for thermal and acoustic benefits. PINK Next Gen™ Fiberglas™ Insulation is dimensionally stable and will not slump within the cavity. Due to its inorganic fibers, PINK Next Gen™ Fiberglas™ Insulation is not a food source for mold, and it is not corrosive to steel, copper, or aluminum.

ASTM C665 CLASSIFICATION	DESCRIPTION
Type I	Blankets without membrane coverings
Type II	Blankets with nonreflective membrane coverings
Class A	Membrane-faced surface flame spread of 25 or less
Class B	Membrane-faced surface with critical radiant flux of 0.12 W/cm ² (0.11 Btu/ft ² xs) or greater
Class C	Membrane-faced surface not rated for flame propagation resistance
Category 1	Membrane is a vapor retarder
Category 2	Membrane is not a vapor retarder
Type III	Blankets with reflective membrane coverings
Class A	Membrane-faced surface flame spread of 25 or less
Class B	Membrane-faced surface with critical radiant flux of 0.12 W/cm ² (0.11 Btu/ft ² xs) or greater
Class C	Membrane-faced surface not rated for flame propagation resistance
Category 1	Membrane is a vapor retarder
Category 2	Membrane is not a vapor retarder

Unfaced — PINK Next Gen™ Fiberglas™ Batt Insulation

Fiberglass insulation designed to improve thermal and acoustic performance of wall and roof/ceiling assemblies. Fits tightly in wood or metal framing to allow for friction-fit installation. Different sizes available to fit specific applications.

- ASTM C665 Type I R-13 3½"
- ASTM E84 <25/<50 R-15 3½"
- ASTM C1338 Mold/ R-19 6½"
- mildew resistant R-20 5½"
- R-21 5½" (6" metal)
- ASTM E136 R-22 6¾"
- Non-Combustible R-23 5½"
- ASTM C518 R-25 8"
- ASTM E90, E413 R-30C 8¼"
- (3½", 5½", 6½") R-30 9½"
- UL File #BKNV R3576 R-38C 10¼"
- (Fire-rated assemblies) R-38 12"
- R-49 14"

Kraft Faced — PINK Next Gen™ Fiberglas™ Batt Insulation

Fiberglass insulation designed to improve thermal and acoustic performance of wall and roof/ceiling assemblies. Fits tightly in wood or metal framing to allow for friction-fit installation. Flanges can be inset or face-stapled as needed. Different sizes available to fit specific applications.

- ASTM C665 Type II, Class C
- ASTM E84 Not rated
- ASTM C1338 Mold/mildew resistant
- ASTM C518
- ASTM E90, E413 (3½", 5½", 6½")
- ASTM E96 Perm Rating — 1 perm
- R-11 3½" R-23 5½"
- R-13 3½" R-30C 8¼"
- R-15 3½" R-30 9½"
- R-19 6½" R-38C 10¼"
- R-20 5½" R-38 12"
- R-21 5½" (6" metal) R-49 14"

Unfaced — PINK Next Gen™ Fiberglas™ Sound Attenuation Batts (SAB) Metal Framing

PINK Next Gen™ Fiberglas™ Insulation designed to improve thermal and acoustic performance of wall and roof/ceiling assemblies. Fits tightly in metal framing to allow for friction-fit installation. Different sizes available to fit specific applications.

- ASTM C665 Type I R-8 2½"
- ASTM E84 <25/<50 R-11 3½"
- ASTM C1338 Mold/mildew resistant R-19 6½"
- ASTM E136 Non-Combustible
- ASTM C518
- ASTM E90, E413 (2½", 3½", 6½")
- UL File #BKNV R3576 (Fire-rated assemblies)

Unfaced — PINK Next Gen™ Fiberglas™ Sound Attenuation Batts (SAB) Wood Framing

PINK Next Gen™ Fiberglas™ Sound Attenuation Batts (SAB) are unfaced, lightweight, flexible fiberglass insulation batts, designed to deliver noise control in wall cavities of interior partitions. Manufactured to friction-fit, they are available in 3½-inch thicknesses.

- ASTM C665 Type 1 R-11 3½"
- ASTM C518
- ASTM E136 Non-combustible
- ASTM C1338 Mold/mildew resistant
- ASTM E119 1-hour fire-resistance rating
- ASTM E84 <25/<50
- ASTM E90, E413
- UL File #BKNV R3576 (fire rated assemblies)

FSK FlameSpread 25 – PINK Next Gen™ Fiberglas™ Insulation

Fiberglass insulation with facing that can be left exposed and is designed to improve thermal and acoustic performance of wall and roof/ceiling assemblies. Fits tightly in wood or metal framing to allow for friction-fit installation. Flanges can be inset or face-stapled as needed. Different sizes available to fit specific applications.

- ASTM C665 Type III (FSK), Class A
- ASTM E84 <25/<50
- ASTM C1338 Mold/mildew resistant
- ASTM C518
- ASTM E96 Perm Rating – 0.5 perm
- UL File #BKNV R3576 (Fire rated assemblies)

FSK

- R-13 3½"
- R-19 6½"
- R-21 6"
- R-30 9½"

Kraft Faced – PROPINK® FastBatt™ Insulation

PINK Next Gen™ Fiberglas™ Insulation designed to improve thermal and acoustic performance of wall and roof/ceiling assemblies. Fits tightly in wood framing to allow for friction-fit installation. Different sizes available to fit specific applications.

- ASTM C665 Type II, Class C
- ASTM E84 Not rated
- ASTM C1338 Mold/mildew resistant
- ASTM C518
- ASTM E96 Perm Rating – 1 perm
- R-13 3½"
- R-15 3½"
- R-19 6½"
- R-21 5½"

Unfaced – PINK Next Gen™ Fiberglas™ Sonobatts® Insulation

PINK Next Gen™ Fiberglas™ Insulation designed to improve thermal and acoustic performance of suspended ceiling assemblies. Size 24 inches by 48 inches to fit on top of most drop-in ceiling tiles.

- ASTM C665 Type I
- ASTM E84 <25/<50
- ASTM C1338 Mold/mildew resistant
- ASTM E136 Non-Combustible
- ASTM C518
- R-19 6.25"

Basement Blanket

Basement Blanket™ Fiberglas™ insulation is recommended for new construction and retrofit basement applications as a means to help reduce heat loss, or gain, through the basement wall area without needing to add a finished wall assembly.

- ASTM C665 Type II, Class A
- ASTM C518
- ASTM C1338 Mold/mildew resistant
- ASTM E84 <25/<50
- R-11 3.5"
- R-19 5.5"

Certifications and Sustainable Features

- Unfaced PINK Next Gen™ Fiberglas™ Insulation and Kraft-Faced PINK Next Gen™ Fiberglas™ Insulation are participating in Declare and are Living Building Challenge Compliant.
- GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg.

Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for, the accuracy or reliability of data associated with particular uses of any product described herein.

SCS Global Services provides independent verification of recycled content in building materials and verifies recycled content claims made by manufacturers. For more information, visit www.SCSglobalservices.com.

OWENS CORNING INSULATING SYSTEMS, LLC

ONE OWENS CORNING PARKWAY
TOLEDO, OH 43659 USA

1-800-GET-PINK® | www.owenscorning.com