



# PINK NEXT GEN™ FIBERGLAS™ ACOUSTIC BATTS INSULATION

## Submittal Sheet

Contractor: \_\_\_\_\_

Project: \_\_\_\_\_

Owens Corning® PINK Next Gen™ Fiberglas™ is flexible, light-density insulation with a variety of facings and uses for thermal and acoustic benefits. PINK Next Gen™ Fiberglas™ is dimensionally stable and will not slump within the cavity. Due to its inorganic fibers, PINK Next Gen™ Fiberglas™ is not a food source for mold, will not rot or mildew, and is not corrosive to steel, copper, or aluminum.

### Unfaced – PINK Next Gen™ Fiberglas™ Thermal Batt Insulation

Fiberglass insulation designed to improve thermal and acoustic performance of wall and roof/ceiling assemblies. Available for use in wood or metal framing. Different sizes available to fit specific applications.

- ASTM C665 Type I, Class A  R-13 3½"
- ASTM E84 <25/<50  R-15 3½"
- ASTM C1338 Mold/mildew resistant  R-19 6½"
- ASTM E136 Noncombustible  R-20 5½"
- ASTM C518  R-21 5½"
- ASTM E90, E413
- UL File #BKNV R3576 (Fire-rated assemblies)

### Unfaced – Sound Attenuation Batts (SAB) Metal Framing

PINK Next Gen™ Fiberglas™ designed to improve thermal and acoustic performance of metal-framed wall and roof/ceiling assemblies. Fits tightly in 16-inch and 24-inch metal framing to allow for friction-fit installation. Different sizes available to fit specific applications.

- ASTM C665 Type I, Class A  R-8 2½"
- ASTM E84 <25/<50  R-11 3½"
- ASTM C1338 Mold/mildew resistant  R-19 6½"
- ASTM E136 Noncombustible
- ASTM C518
- ASTM E90, E413
- UL File #BKNV R3576 (Fire-rated assemblies)

### Unfaced – Sonobatts® Insulation

PINK Next Gen™ Fiberglas™ Insulation designed to improve thermal and acoustic performance of suspended ceiling assemblies. Size 24 inches by 48 inches to fit on top of most drop-in ceiling tiles.

- ASTM C665 Type I, Class A  R-19 6½"
- ASTM E84 <25/<50
- ASTM C1338 Mold/mildew resistant
- ASTM E136 Noncombustible
- ASTM C518
- ASTM E1414
- UL File #BKNV R3576

### Sound Attenuation Batts (SAB) Wood Framing

PINK Next Gen™ Fiberglas™ Sound Attenuation Batts (SAB) are unfaced, lightweight, flexible fiberglass insulation batts, designed to deliver noise control in wall cavities of interior partitions. Manufactured to friction-fit, they are available in 3½-inch thicknesses. Depending on the construction method and components used, SABs can improve STC (Sound Transmission Class) ratings by 2–11 points over an empty cavity.<sup>1</sup>

- ASTM C665 Type 1  R-11 3½"
- ASTM C518
- ASTM E136 Non-combustible
- ASTM C1338 Mold/mildew resistant
- ASTM E84 <25/<50
- ASTM E90, E413
- UL File #BKNV R3576 (Fire-rated assemblies)

<sup>1</sup> Depending on framing cavity options.

	UL #	Acoustic Test #	STC	Assembly
	UL-U494	NRC-TL-93-058	39	1 layer, 5/8" each side, 2½" studs, 16" OC, 2½" FB
	UL-W405	NRC-TL-93-351	50	1 layer, 5/8" each side, 3½" studs, 16" OC, 3½" FB
	UL-U465	NRC-TL-93-298	51	1 layer, 5/8" each side, 6" studs, 16" or 24" OC, 6" FB
	UL-U340	NRC-TL-93-248	49	1 layer, 5/8" each side, 3½" studs, 16" or 24" OC, 3½" FB
	OSUT-3127 NBC-W3a & 3b	NRC-TL-93-098	50	1 layer, 5/8" each side, 16" or 24" OC, 3½" FB, RC 24" OC
	GA-WP-3370 NBC-W13a	NRC-TL-93-266	56	1 layer, 5/8" each side, 16" or 24" OC, 3½" FB
	ULC-W301 NBC-W1a	W2069	39	1 layer, ½" each side, 16" OC, 3½" FB

Note: Wall assemblies with thermal batts provide acoustic ratings (STC) that are very similar to ratings of wall assemblies with acoustic batts.

### **Certifications and Sustainable Features**

- Unfaced PINK Next Gen™ Fiberglas™ Insulation and Kraft-Faced PINK Next Gen™ Fiberglas™ Insulation are participating in Declare and are Living Building Challenge Compliant.
  - Certified by SCS Global Services to contain an average of 55% recycled glass content, 18% pre-consumer, and 37% post-consumer.
  - GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit [ul.com/gg](http://ul.com/gg).
  - Environmental Product Declaration (EPD) has been certified by UL Environment.
  - PINK Next Gen™ Fiberglas™ Insulation products have a published Health Product Declaration (HPD).
- 

### **Disclaimer of Liability**

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for, the accuracy or reliability of data associated with particular uses of any product described herein.

SCS Global Services provides independent verification of recycled content in building materials and verifies recycled content claims made by manufacturers. For more information, visit [www.SCSglobalservices.com](http://www.SCSglobalservices.com).