FOAMGLAS®

PITTWRAP® SS PRIMER



Description and Area of Application

PITTWRAP® SS Primer is specially formulated to promote adhesion of self-sealing, bituminous PITTWRAP® jacketing when the laps are slightly dusty or the temperature at application is between -7 and 10°C (20 and 50°F).

Field Application

- Always read and understand information contained within product data sheets and safety data sheets before attempting to use this product. If you have questions regarding fitness of use of this product for a particular application, consult Owens Corning.
- Apply a thin coat of primer to the bituminous side of the jacketing lap with a brush or swab. Press lap and roll the completed joint with a hard roller, such as a wallpaper seam roller.
- Check for unsealed areas along the seam and repress or reseal before back filling. Refer to specific self-sealing PITTWRAP® jacketing product data sheets for details of jacketing application.

Type of Delivery and Storage

- 3.8 L (1 gal) can. Approximate weight 4.08 kg (9 lb) per can.
- Store in a well-ventilated room away from ignition sources.
- Store closed containers between -15°C to 35°C (5°F to 95°F). Freeze protect shipping not required.
- Ground all metal containers.

Coverage

- Determine the amount of primer needed by calculating the surface area to be coated. Using the surface area to estimate the amount of PITTWRAP® SS Primer needed based on the coverage listed below.
- PITTWRAP® SS PRIMER Coverage: 3m^2/L (125ft^2/gal)

Note: Figures DO NOT include losses. Typically, adding 10% to coverage area will account for losses.

Limitations

- It is used only to assist in making a bond.
- Use only on the bituminous side of the jacketing.
- Solvent may attack organic foams.

Typical Properties

PROPERTY[1]	ASTM METHOD	SI	ENGLISH
Color	-	Black	
Solids Content, Volume	-	72%	
Flash Point	TCC	27°C	80°F
Application Temperature	-	15.5 ± 22.5°C	60 ± 40°F
Reaction to Fire Wet Dry	-	Flammable Combustible	
Solvent	-	Xylene	

1 Properties subject to change. Consult Owens Corning.

For additional information on PITTWRAP® SS PRIMER or systems, please contact Owens Corning at any of our worldwide offices or visit us at www.owenscorning.com.

The information contained herein is accurate and reliable to the best of our knowledge. But, because Pittsburgh Corning, LLC has no control over installation workmanship, accessory materials, or conditions of application, NO EXPRESSED OR IMPLIED WARRANTY OF ANY KIND, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, IS MADE as to the performance of an installation containing Owens Corning products. In no event shall Pittsburgh Corning, LLC be liable for any damages arising because of product failure, whether incidental, special, consequential, or punitive, regardless of the theory of liability upon which any such damages are claimed. Pittsburgh Corning, LLC provides written warranties for many of its products, and such warranties take precedence over the statements contained herein.

Industrial & Commercial Sales

Americas
+1 800 327 6126

Asia-Pacific
Singapore: +65 9635 9184
China: +86 (0) 21 6101 7179
Japan: +81 3 6365 4307

Europe, Middle East & Africa
+32 13 661 721

Technical Services

Americas & Asia-Pacific
+1 800 327 6126
foamglastechnical@owenscorning.com

Europe, Middle East & Africa
+32 13 611 468
industry.tech@owenscorning.com

FOAMGLAS®

PITTSBURGH CORNING, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OH 43659 USA

Toll Free + 1 800 327 6126
For web-based Sales and Technical Service inquiries, please visit **www.owenscorning.com**.

Pub. No. 10025074-A. July 2026.

© 2026 Owens Corning. All Rights Reserved.
© 2026 Pittsburgh Corning, LLC. All Rights Reserved.