



PINK NEXT GEN® FIBERGLAS™ INSULATION

This fact sheet contains important details about Owens Corning® Pink Next Gen® Fiberglas™ Insulation. The chart below covers the entire line of Pink Next Gen® products sold under the names FastBatt™, Cathedral Batt, Basement Blanket™, Sound Attenuation Batt (SAB), Flame Spread 25, and Sonobatts®. The chart includes all products, both unfaced and faced with Kraft paper, polyethylene ("Poly"), or FSK.

MANUFACTURERS FACT SHEET

FACING	R-VALUE	WIDTH (INCHES)	LENGTH (INCHES)	THICKNESS (INCHES)	PIECE SQ. FT.	PIECES/ PACKAGE	PACKAGE SQ. FT.
U	8	24	96	2.5"	16	20	320
U	8	16	96	2.5"	10.7	20	213.33
U	11	15.25	93	3.5"	9.8	16	157.583
U	11	23.25	93	3.5"	15	16	240.25
U	11	15.25	105	3.5"	11.1	16	177.917
U	11	24	96	3.5"	16	16	256
U	11	16	96	3.5"	10.7	16	170.67
U	11	48	600	3.5"	200	1	200
K	11	23	93	3.5"	14.9	13	193.104
K	11	15	93	3.5"	9.7	13	125.94
P	11	48	600	3.5"	200	1	200
U	13	23	93	3.5"	14.9	12	178.25
U	13	24	96	3.5"	16	12	192
U	13	16	96	3.5"	10.7	11	117.34
U	13	15	105	3.5"	10.9	11	120.31
U	13	15	93	3.5"	9.7	11	106.56
K	13	15	105	3.5"	10.9	12	131.25
K	13	15	93	3.5"	9.7	13	125.94
K	13	16	96	3.5"	10.7	13	138.67
K	13	23	93	3.5"	14.9	10	148.54
K	13	15	384	3.5"	40	1	40
FB	13	15.25	93	3.5"	9.8	13	128.04
FB	13	15.25	105	3.5"	11.1	12	133.44

FACING	R-VALUE	WIDTH (INCHES)	LENGTH (INCHES)	THICKNESS (INCHES)	PIECE SQ. FT.	PIECES/ PACKAGE	PACKAGE SQ. FT.
FSK	13	24	96	3.5"	16	11	176
FSK	13	16	96	3.5"	10.7	11	117.34
U	15	23	93	3.5"	14.9	7	103.98
U	15	16	96	3.5"	10.7	7	74.69
U	15	24	96	3.5"	16	7	112
U	15	15	105	3.5"	10.9	8	87.5
U	15	15	93	3.5"	9.7	8	77.5
K	15	23	93	3.5"	14.9	7	103.98
K	15	16	96	3.5"	10.7	7	74.67
K	15	15	93	3.5"	9.7	7	67.81
FB	15	15.25	93	3.5"	9.8	8	78.792
FB	15	15	105	3.5"	10.9	8	87.5
U	19	15	48	6.5"	5	16	80
U	19	24	48	6.25"	8	16	128
U	19	15	105	6.5"	10.9	8	87.5
U	19	16	96	6.5"	10.7	8	85.33
U	19	19.25	48	6.5"	6.4	16	102.67
U	19	15	93	6.5"	9.7	8	77.5
U	19	15	470	6.25"	49	1	48.96
U	19	23	470	6.25"	75.1	1	75.07
U	19	23	93	6.5"	14.9	8	118.83
U	19	24	96	6.5"	16	8	128
U	19	48	360	5.5"	120	1	120

READ THIS BEFORE YOU BUY

What you should know about R-values

The chart shows the R-values of this insulation. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy.

There are other factors to consider. The amount of insulation you need depends mainly on the climate you live in. Also, your fuel savings from insulation will depend on the climate, the type and size of house, the amount of insulation already in your house, and your fuel-use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on fuel.

To get the marked R-value, it is essential that this insulation be installed properly.

- K Standard Kraft Facing - must be in contact with therma/barrier
- U UnfacedFSK - Foil Scrim Kraft - can be left exposed
- P Poly - Perforated Poly for basement walls
- FB FastBatt - Kraft with no flanges. Friction fit.

FACING	R-VALUE	WIDTH (INCHES)	LENGTH (INCHES)	THICKNESS (INCHES)	PIECE SQ. FT.	PIECES/ PACKAGE	PACKAGE SQ. FT.
P	19	48	360	5.5"	120	1	120
K	19	15	105	6.5"	10.9	8	87.5
K	19	16	96	6.5"	10.7	8	85.33
K	19	24	96	6.5"	16	8	128
FB	19	15.25	93	6.5"	9.8	8	78.79
K	19	23	93	6.5"	14.9	8	118.83
K	19	15	93	6.5"	9.7	8	77.5
K	19	19.25	48	6.5"	6.4	16	102.67
K	19	23	470	6.25"	75.1	1	75.07
K	19	15	470	6.25"	49	1	48.96
FB	19	15.25	105	6.5"	11.1	8	88.96
FSK	19	16	96	6.5"	10.7	8	85.33
FSK	19	24	96	6.5"	16	8	128
U	20	15	93	5.5"	9.7	8	77.5
U	20	15	105	5.5"	10.9	8	87.504
K	20	15	93	5.5"	9.7	8	77.5
U	21	16	96	6"	10.7	7	74.67
U	21	24	96	6"	16	7	112
U	21	23.25	93	5.5"	15	6	90.094
U	21	23	93	5.5"	14.9	6	89.13
U	21	15	93	5.5"	9.7	8	77.5
U	21	15.25	93	5.5"	9.8	7	68.94
K	21	15	93	5.5"	9.7	7	67.81
K	21	23	93	5.5"	14.9	6	89.13
K	21	16	96	6"	10.7	7	74.67
K	21	15	105	5.5"	10.9	8	87.5
U	21	15	105	5.5"	10.9	8	87.5
FB	21	15	105	5.5"	10.9	8	87.5
FB	21	15.25	93	5.5"	9.8	7	68.94
FB	21	15.25	105	5.5"	11.1	7	77.84
FSK	21	16	96	6"	10.7	7	74.67
U	22	24	48	6.75"	8	14	112
U	22	23	48	6.75"	7.7	14	107.34
U	23	15	93	5.5"	9.7	5	48.438
U	23	15	105	5.5"	10.9	5	54.688

FACING	R-VALUE	WIDTH (INCHES)	LENGTH (INCHES)	THICKNESS (INCHES)	PIECE SQ. FT.	PIECES/ PACKAGE	PACKAGE SQ. FT.
K	23	15	105	5.5"	10.9	5	54.688
K	23	15	93	5.5"	9.7	5	48.438
U	25	24	96	8"	16	6	96
U	25	16	96	8"	10.7	6	64
U	30	19.25	48	9.5"	6.4	10	64.17
U	30	16	48	9.5"	5.3	10	53.33
U	30	24	48	9.5"	8	10	80
U	30	15	300	9"	31.3	1	31.25
U	30	23	300	9"	47.9	1	47.92
K	30	19.25	48	9.5"	6.4	10	64.17
K	30	16	48	9.5"	5.3	11	58.67
K	30	24	48	9.5"	8	11	88
FSK	30	16	48	9.5"	5.3	10	53.33
FSK	30	24	48	9.5"	8	10	80
U	38	16	48	12"	5.3	8	42.67
U	38	19.25	48	12"	6.4	8	51.33
U	38	24	48	12"	8	8	64
K	38	16	48	12"	5.3	8	42.67
K	38	24	48	12"	8	8	64
U	30C	23.75	48	8.25"	7.9	10	79.17
U	30C	15.5	48	8.25"	5.2	11	56.83
K	30C	23.75	48	8.25"	7.9	10	79.17
K	30C	15.5	48	8.25"	5.2	11	56.83
U	38C	15.5	48	10.25"	5.2	8	41.33
U	38C	23.75	48	10.25"	7.9	8	63.33
K	38C	23.75	48	10.25"	7.9	8	63.33
K	38C	15.5	48	10.25"	5.2	8	41.33
U	49	24	48	14"	8	6	48
K	49	16	48	14"	5.3	6	32
K	49	24	48	14"	8	6	48

- K Standard Kraft Facing - must be in contact with therma/barrier
- U UnfacedFSK - Foil Scrim Kraft - can be left exposed
- P Poly - Perforated Poly for basement walls
- FB FastBatt - Kraft with no flanges. Friction fit.

OWENS CORNING INSULATING SYSTEMS, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OH 43659 USA
1-800-GET-PINK®
www.owenscorning.com