



PINK NEXT GEN[®] FIBERGLAS[™] INSULATION

This fact sheet contains important details about Owens Corning[®] Pink Next Gen[®] Fiberglas[™] Insulation. The chart below covers the entire line of Pink Next Gen[®] products sold under the names FastBatt[™], Cathedral Batt, Basement Blanket[™], Sound Attenuation Batt (SAB), Flame Spread 25, and Sonobatts[®]. The chart includes all products, both unfaced and faced with Kraft paper, polyethylene ("Poly"), or FSK.

MANUFACTURERS FACT SHEET

R-VALUE	LENGTH (INCHES)	WIDTH (INCHES)	THICKNESS (INCHES)	PIECE SQ. FT.	PIECES/PACKAGE	PACKAGE SQ. FT.
8	24	96	2.5"	16	20	320
8	16	96	2.5"	10.7	20	213.33
11	15.25	93	3.5"	9.8	16	157.583
11	23.25	93	3.5"	15	16	240.25
11	15.25	105	3.5"	11.1	16	177.917
11	24	96	3.5"	16	16	256
11	16	96	3.5"	10.7	16	170.67
11	48	600	3.5"	200	1	200
11	23	93	3.5"	14.9	13	193.104
11	15	93	3.5"	9.7	13	125.94
11	48	600	3.5"	200	1	200
13	23	93	3.5"	14.9	12	178.25
13	24	96	3.5"	16	12	192
13	16	96	3.5"	10.7	11	117.34
13	15	105	3.5"	10.9	11	120.31
13	15	93	3.5"	9.7	11	106.56
13	15	105	3.5"	10.9	12	131.25
13	15	93	3.5"	9.7	13	125.94
13	16	96	3.5"	10.7	13	138.67
13	23	93	3.5"	14.9	10	148.54
13	15	384	3.5"	40	1	40
13	15.25	93	3.5"	9.8	13	128.04
13	15.25	105	3.5"	11.1	12	133.44

R-VALUE	LENGTH (INCHES)	WIDTH (INCHES)	THICKNESS (INCHES)	PIECE SQ. FT.	PIECES/PACKAGE	PACKAGE SQ. FT.
13	24	96	3.5"	16	11	176
13	16	96	3.5"	10.7	11	117.34
15	23	93	3.5"	14.9	7	103.98
15	16	96	3.5"	10.7	7	74.69
15	24	96	3.5"	16	7	112
15	15	105	3.5"	10.9	8	87.5
15	15	93	3.5"	9.7	8	77.5
15	23	93	3.5"	14.9	7	103.98
15	16	96	3.5"	10.7	7	74.67
15	15	93	3.5"	9.7	7	67.81
15	15.25	93	3.5"	9.8	8	78.792
15	15	105	3.5"	10.9	8	87.5
19	15	48	6.5"	5	16	80
19	24	48	6.25"	8	16	128
19	15	105	6.5"	10.9	8	87.5
19	16	96	6.5"	10.7	8	85.33
19	19.25	48	6.5"	6.4	16	102.67
19	15	93	6.5"	9.7	8	77.5
19	15	470	6.25"	49	1	48.96
19	23	470	6.25"	75.1	1	75.07
19	23	93	6.5"	14.9	8	118.83
19	24	96	6.5"	16	8	128
19	48	360	5.5"	120	1	120

READ THIS BEFORE YOU BUY

What you should know about R-values

The chart shows the R-values of this insulation. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy.

There are other factors to consider. The amount of insulation you need depends mainly on the climate you live in. Also, your fuel savings from insulation will depend on the climate, the type and size of house, the amount of insulation already in your house, and your fuel-use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on fuel.

To get the marked R-value, it is essential that this insulation be installed properly.

R-VALUE	THICKNESS (INCHES)	WIDTH (INCHES)	LENGTH (INCHES)	PIECE SQ. FT.	PIECES/PACKAGE	PACKAGE SQ. FT.
19	48	360	5.5"	120	1	120
19	15	105	6.5"	10.9	8	87.5
19	16	96	6.5"	10.7	8	85.33
19	24	96	6.5"	16	8	128
19	15.25	93	6.5"	9.8	8	78.79
19	23	93	6.5"	14.9	8	118.83
19	15	93	6.5"	9.7	8	77.5
19	19.25	48	6.5"	6.4	16	102.67
19	23	470	6.25"	75.1	1	75.07
19	15	470	6.25"	49	1	48.96
19	15.25	105	6.5"	11.1	8	88.96
19	16	96	6.5"	10.7	8	85.33
19	24	96	6.5"	16	8	128
20	15	93	5.5"	9.7	8	77.5
20	15	105	5.5"	10.9	8	87.504
20	15	93	5.5"	9.7	8	77.5
21	16	96	6"	10.7	7	74.67
21	24	96	6"	16	7	112
21	23.25	93	5.5"	15	6	90.094
21	23	93	5.5"	14.9	6	89.13
21	15	93	5.5"	9.7	8	77.5
21	15.25	93	5.5"	9.8	7	68.94
21	15	93	5.5"	9.7	7	67.81
21	23	93	5.5"	14.9	6	89.13
21	16	96	6"	10.7	7	74.67
21	15	105	5.5"	10.9	8	87.5
21	15	105	5.5"	10.9	8	87.5
21	15	105	5.5"	10.9	8	87.5
21	15.25	93	5.5"	9.8	7	68.94
21	15.25	105	5.5"	11.1	7	77.84
21	16	96	6"	10.7	7	74.67
22	24	48	6.75"	8	14	112
22	23	48	6.75"	7.7	14	107.34
23	15	93	5.5"	9.7	5	48.438
23	15	105	5.5"	10.9	5	54.688

R-VALUE	THICKNESS (INCHES)	WIDTH (INCHES)	LENGTH (INCHES)	PIECE SQ. FT.	PIECES/PACKAGE	PACKAGE SQ. FT.
23	15	105	5.5"	10.9	5	54.688
23	15	93	5.5"	9.7	5	48.438
25	24	96	8"	16	6	96
25	16	96	8"	10.7	6	64
30	19.25	48	10"	6.4	10	64.17
30	16	48	10"	5.3	10	53.33
30	24	48	10"	8	10	80
30	15	300	9"	31.3	1	31.25
30	23	300	9"	47.9	1	47.92
30	19.25	48	10"	6.4	10	64.17
30	16	48	10"	5.3	11	58.67
30	24	48	10"	8	11	88
30	16	48	10"	5.3	11	58.67
30	24	48	10"	8	11	88
30	16	48	10"	5.3	10	53.33
30	24	48	10"	8	10	80
38	16	48	12"	5.3	8	42.67
38	19.25	48	12"	6.4	8	51.33
38	24	48	12"	8	8	64
38	16	48	12"	5.3	8	42.67
38	24	48	12"	8	8	64
30C	23.75	48	8.25"	7.9	10	79.17
30C	15.5	48	8.25"	5.2	11	56.83
30C	23.75	48	8.25"	7.9	10	79.17
30C	15.5	48	8.25"	5.2	11	56.83
38C	15.5	48	10.25"	5.2	8	41.33
38C	23.75	48	10.25"	7.9	8	63.33
38C	23.75	48	10.25"	7.9	8	63.33
38C	15.5	48	10.25"	5.2	8	41.33
49	24	48	14"	8	6	48
49	16	48	14"	5.3	6	32
49	24	48	14"	8	6	48

OWENS CORNING INSULATING SYSTEMS, LLC
 ONE OWENS CORNING PARKWAY
 TOLEDO, OH 43659 USA
1-800-GET-PINK®
www.owenscorning.com