



TURBOSTRAND® 4595 SINGLE-END ROVING

Solution for dependable processing with PA&PC LFT and CFRT

Type 30® TurboStrand® 4595 single-end roving is specifically designed for excellent processing and handling for LFT (long fiber reinforced thermoplastic) & CFRT (continuous fiber reinforced thermoplastics) polyamide and polycarbonate applications.

- ✓ Manufactured using state-of-the-art Owens Corning® Type 30® Single-End-Roving technology.
- ✓ Produced via statistical process control in manufacturing facilities certified to ISO 9001.
- ✓ Excellent compatibility with polyamide and polycarbonate.
- ✓ Produced with Advantex® corrosion-resistant E-CR glass by Owens Corning.

Product Benefits

- Enhanced Mechanical Performance**
 - TurboStrand® 4595 offers enhanced composite tensile, flexural, and impact performance. Providing maximum part strength and long part service life.
- Improved Manufacturing Economics**
 - Dependable internal and external unwinding process for less downtime.
 - Reduction in fuzz generation for easier processing and less downtime for cleanup, also resulting in a smoother finished product.
- Enhanced Service Life**
 - Advantex® glass helps fight corrosion, enhancing service life compared to standard E-glass.
- Excellent Impregnation & Dispersion**
 - High-quality dispersion within the pellet and final mold, creating excellent surface appearance and part strength.
- Multi-Process Compatible**
 - Suitable for LFT-G, D-LFT, and CFRT processes and pellet manufacturing, and choppable to desired length.

Application

TurboStrand® 4595 is ideal for polyamide and polycarbonate long-fiber thermoplastic applications with LFT-G, D-LFT, and CFRT. Designed for the manufacturing of structural automotive applications, including instrument panel framework and EV battery cover. Potential application for TurboStrand® 4595 is TP fabrics for wind blades and RTP (reinforced thermoplastic pipes), which can be recycled and economical.

Availability & Technical Characteristics

TEX	FILAMENT DIAMETER (μ)	LOSS ON IGNITION (%)	MOISTURE (% MAX)	MANUFACTURING REGION
2400	17	0.40%	0.05%	Asia Pacific
1200	17	0.40%	0.05%	Asia Pacific

Packaging

PALLET DIMENSIONS

PACKAGING	PALLET HEIGHT (CM)	PALLET LENGTH (CM)	PALLET WIDTH (CM)	PALLET WEIGHT (NET, KG)	PACKAGES PER PALLET	NUMBER OF LAYERS
No Tube	~ 125	115	115	~ 1200	64	4
No Tube	~ 97	115	115	~ 900	48	3
Thicker Tube	~ 200	115	115	~ 900	48	3

PACKAGE DIMENSIONS

PACKAGE HEIGHT (CM)	PACKAGE OUTSIDE DIAMETER (CM)	PACKAGE INSIDE DIAMETER (CM)		PACKAGE WEIGHT (KG, WEIGHT% IN PALLET)		
<28.0	<30.0	>16.2 (no tube)	-16.2 (thick tube)	16-20 (70%)	10-16 (25%)	5-10 (5%)

Labeling

Each individual package is labeled with information including: product name, tex/yield, producing plant, and production date.

Storage

Unless otherwise specified, it is recommended to store glass fiber products in a cool, dry area. The glass fiber products must remain in their original packaging material until the point of usage. The product should be stored in the workshop in its original packaging for 48 hours prior to its utilization, to allow it to reach the workshop temperature condition and prevent condensation, especially during the cold season. The packaging is not waterproof. Be sure to protect the product from the weather and other sources of water.

When stored properly, there is no known shelf life to the product, but retesting is advised after two years from the initial production date to ensure optimum performance.

**MAKE
MORE
POSSIBLE™**

Asia Pacific
40/F, Pudong Kerry Parkside,
115 Fang Dian Road, Pudong,
Shanghai, 201204, China
+86-21-61019666

This information and data contained herein is offered solely as a guide in the selection of product. We believe this information to be reliable but do not guarantee its applicability to the user's process or assume any responsibility or liability arising out of its use or performance. The user agrees to be responsible for thoroughly testing any application of the product to determine its suitability. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose. Statements in this publication shall not be construed as representations or warranties or as inducements to infringe on any patent or violate any law, safety code, or insurance regulation. We reserve the right to modify this document without prior notice.

Pub. No. 10025666. TurboStrand® 4595 Product Data Sheet. December 2025. English. © 2026 Owens Corning. All Rights Reserved.