




# PULTRUSION

These products are often used in pultrusion processes in a variety of parts, such as poles and pipes, rebar, windows and doors, cross-arms, and sucker rods, among others. They are utilized across several applications with a range in thickness and diameter. Some of their most important characteristics are processing efficiency, mechanical performance, and surface aesthetics. The production process includes corrosion-resistant Advantex® E-CR glass by Owens Corning.



**PROCESSABILITY**



**SURFACE AESTHETICS**



**HIGH MECHANICAL PERFORMANCE**

	<b>PulStrand 4100</b>	<b>PulStrand PRO41</b>	<b>366</b>	<b>PulStrand 2100</b>	<b>SE1200</b>
<b>RESINS</b>	Epoxy, Polyester, Vinyl Ester, Polyurethane	Epoxy, Polyester, Vinyl Ester, Polyurethane	Epoxy, Polyester, Vinyl Ester, Polyurethane	Epoxy, Polyester, Vinyl Ester, Polyurethane	Epoxy, Polyester, Vinyl Ester, Polyurethane, Polyamide
<b>TEX RANGE</b>	2000–9600	17,716	1100–4400	8800	275–4400
<b>APPLICATION</b>	<b>GENERAL PURPOSE</b>	✓✓✓	✓✓✓		✓✓
	<b>STRUCTURAL</b>	✓✓	✓✓✓	✓✓✓	
	<b>LADDER RAILS</b>	✓✓✓		✓✓✓	
	<b>TELECOM – UV</b>				✓✓
	<b>TELECOM – FLEX</b>				✓✓✓

**Americas**

**Owens Corning Composite Materials, LLC**  
 One Owens Corning Parkway  
 Toledo, OH 43659 USA  
 1-800-GET-PINK®

**Europe**

**European Owens Corning Fibreglas Sprl.**  
 166 Chaussée de la Hulpe  
 B-1170 Brussels  
 Belgium  
 +32 3 674 8211

**Asia Pacific**

**Owens Corning Shanghai Regional Headquarters**  
 40/F, Pudong Kerry Parkside,  
 115 Fang Dian Road, Pudong,  
 Shanghai, 201204, China  
 +86-21-6101 9666

**VIEW OUR PULTRUSION PROCESS VIDEO**



<https://www.owenscorning.com/composites> | 1-800-GET-PINK®

This information and data contained herein is offered solely as a guide in the selection of product. We believe this information to be reliable but do not guarantee its applicability to the user's process or assume any responsibility or liability arising out of its use or performance. The user agrees to be responsible for thoroughly testing any application of the product to determine its suitability. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose. Statements in this publication shall not be construed as representations or warranties or as inducements to infringe on any patent or violate any law, safety code, or insurance regulation. We reserve the right to modify this document without prior notice.