



FOAMULAR® NGX®

Project

INTERIOR ABOVE/BELOW GRADE WALL (MASONRY)

Recommended Products

FOAMULAR® 150

2"-3" thickness to meet Energy Code minimums

Accessory Products

1"x3" furring strips

Basic Tools


- Tape measure
- Utility knife
- Straightedge
- Caulk gun (for adhesive)
- Hammer
- Hammer drill/power screwdriver
- 6" drywall saw

Protective Gear

- Cut-resistant gloves
- OSHA approved safety glasses

Special Equipment

- Power or powder actuated concrete fastening tool



Site Preparations

1. Ensure that the substrate is clean and dry. Remedy all protrusions or surfaces that are not flat.
*For framed applications. Check that framing provides a flat, level surface. Repair or replace any warped or damaged framing.
2. Remove obstacles to the work area including all potential trip hazards.
3. Verify that ladders and/or scaffolding are in safe, working condition.



FOAMULAR® NGX®

Installation Instructions

1. Repair any leaks or flashing details prior to installing FOAMULAR®.
2. Start in corner. Typically installed vertically with edges of FOAMULAR® tightly butted.
3. Seams do not require sealing.
4. Verify thickness of FOAMULAR® or additional insulation required to meet minimum Energy Code.

Option 1 (FOAMULAR® 150)

1. Attach FOAMULAR® to masonry wall with 3/16" bead of adhesive with lines 6-12" apart. Cure time may vary. Consult adhesive instructions for additional information.
2. Frame out studded wall in contact with the FOAMULAR®, anchoring to floor and floor framing above.
3. Kraft faced or unfaced cavity insulation can be used in the framing (optional).
4. Attach gypsum drywall to framing.

Additional Considerations

- This product is not required to be installed by someone trained or certified by the manufacturer.
- As is, this product undergoes no chemical reaction and is in its final form when purchased. There is no need to evacuate the building during installation.
- FOAMULAR® cannot be in contact with hot surfaces such as chimneys or heat sources over 165 degrees F.
- Air Sealing—in applications that require air sealing, use Owens Corning® HomeSealR™ foam joint tape to seal joints between boards. Use Owens Corning® FlashSealR® foam flashing tape to seal FOAMULAR® to other substrates.
- Use HomeSealR™ to repair breaks. Replace foam into the board and then tape with HomeSealR™ to repair holes.
- Avoid leaving FOAMULAR® exposed for extended periods of time.
- For use in exposed applications refer to Code Evaluation Report UL-ER8811-01 and local building codes regarding the need for an ignition barrier.
- To cut boards to size, score with box knife then snap at the score.
- Use a 6" drywall saw to cut holes or other penetrations through the FOAMULAR®.

OWENS CORNING FOAM INSULATION, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OH 43659 USA

1-800-GET-PINK®
www.owenscorning.com

Pub. No. 10026629-A. Printed in the U.S.A. July 2026.
THE PINK PANTHER™ & © 1964–2026 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved.
The color PINK is a registered trademark of Owens Corning. © 2026 Owens Corning. All Rights Reserved.