



TECHNICAL BULLETIN

ATTICAT® BAGS IN WALL APPLICATION

SUMMARY

AttiCat® is a loosefill insulation system intended for contractor and homeowner use. It is a system with a specific machine and bags intended for use with that machine. It is designed and intended for use in "open blow" applications, typically attics. The AttiCat® blowing machine is not intended or designed to blow enclosed cavities, such as walls.

The AttiCat® insulation bags however can be used in wall applications when blown through a blowing machine like those from Krendl, ACCU1 and others. The AttiCat bags are designed for use with the AttiCat® machine but can easily be added to truck mount/commercial machines in the same manner as the typical bags used in these machines.

The weight of the bag is different from our L77 bag so the below table will need to be referenced to determine R-value, density, bags per 1000 sq. ft. and coverage per bag.

WALL CHART

AttiCat® 27.5lb Bag

R-VALUE	FRAMING	ACTUAL THICKNESS	DENSITY (LBS/CF)	COVERAGE PER BAG (SF)	BAGS PER 1000 SF	MIN WT (LBS/SF)
14	2x4	3.5	1.3	72.5	13.8	0.379
15	2x4	3.5	1.6	58.9	17.0	0.467
23	2x6	5.5	1.4	42.9	23.3	0.642
24	2x6	5.5	1.9	31.6	31.7	0.871

Disclaimer of Liability

Technical Information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein. Nothing contained in this bulletin shall be considered a recommendation.

OWENS CORNING FOAM INSULATION, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OH 43659 USA

1-800-GET-PINK®

www.owenscorning.com