



INSULGUARD™

Unfaced Water Heater Insulation

Thermal and Acoustical Insulation



Owens Corning InsulGuard™ Unfaced Water Heater Insulation is designed specifically for residential and commercial water heater applications. InsulGuard™ Unfaced Insulation is ideal for either gas or electric water heater applications where high temperature requirements are necessary with limited space availability.

Owens Corning InsulGuard™ Unfaced Insulation is offered in a wide range of thicknesses between 3/8" and 1" and can be used in operating temperatures up to 1000°F. InsulGuard™ Unfaced Water Heater Insulation is a lightweight, flexible product providing ease of handling in both fabricating and installation.

Thermal Conductivity

Owens Corning InsulGuard™ Unfaced Water Heater Insulation

Thickness	Nominal K Value			Nominal K. W/mK		
	75°F	150°F	300°F	23°C	65°C	149°C
0.75"	0.22	0.25	0.30	0.032	0.036	0.044
1.0"	0.22	0.25	0.29	0.032	0.036	0.044
1.25"	0.22	0.25	0.29	0.032	0.036	0.044

1. Thickness value is nominal. Product control is on thermal conductivity.

Features

- Thin insulation offers an option for areas where high-temp insulation is required in narrow spaces
- Manufactured without formaldehyde
- User friendly fibers result in less dust levels and less itch and irritation for installers in comparison to binder based products
- Up to 1000°F operating temperatures for unfaced insulation
- Improved K allows thinner insulation to provide same R-value
- Certified high recycled content 53%

Applications

Owens Corning InsulGuard™ Unfaced Water Heater Insulation is a unique and proprietary blend of fiber sciences and manufacturing technology resulting in a product with excellent thermal performance for use with both gas and electric water heaters.

- Insulation for Residential Water Heaters
- Insulation for Commercial Water Heaters
- Foam Stops
- Tank Insulation
- Gaskets
- Chamber Wraps
- Thermal Panels

Availability

Owens Corning InsulGuard™ Unfaced Water Heater Insulation offers a broad range of thickness options below 1". Products are available in numerous thicknesses; minimum 3/8" up to 1" in 1/8" increments. Foil and multiple other facings may be available upon request.

Standards, Codes Compliance

- Owens Corning InsulGuard™ Unfaced Water Heater Insulation is non-corrosive to steel (per ASTM C665)
- Owens Corning InsulGuard™ Unfaced Water Heater Insulation has flame spread/smoke developed indices less than 25/50 per ASTM E84/UL 723 (Unfaced Owens Corning InsulGuard™ Unfaced Water Heater Insulation is UL listed)
- Owens Corning InsulGuard™ Unfaced Water Heater Insulation has an operating temperature up to 1000°F (538°C) for unfaced materials (per ASTM C411).

Environmental and Sustainability

Owens Corning is a worldwide leader in building material systems, insulation and composite solutions, delivering a broad range of high-quality products and services. Owens Corning is committed to driving sustainability by delivering solutions, transforming markets and enhancing lives.

More information can be found at www.owenscorning.com.

Notes

For additional information, refer to the Safe Use Instruction Sheet (SUIS) found in the SDS Database via <http://sds.owenscorning.com>

Certifications and Sustainable Features

- Certified by SCS Global Services to contain a minimum of 53% recycled glass content, 31% pre-consumer and 22% post-consumer
- GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg
- Environmental Product Declaration (EPD) has been certified by UL Environment
- Material Health Certificate from Cradle to Cradle Products Innovation Institute



Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein. SCS Global Services provides independent verification of recycled content in building materials and verifies recycled content claims made by manufacturers. For more information, visit www.SCSglobalservices.com.

LEED® is a registered trademark of the U.S. Green Building Council.

For more information visit our appliance website
[https://www.owenscorning.com/en-us/insulation/commercial/oc-appliance](http://www.owenscorning.com/en-us/insulation/commercial/oc-appliance)

OWENS CORNING INSULATING SYSTEMS, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OH 43659 USA
1-800-GET-PINK®
www.owenscorning.com

Pub. No. 10027312-CC. Printed in U.S.A. July 2024.
The color PINK is a registered trademark of Owens Corning. © 2023 Owens Corning. All Rights Reserved.