



# NATURAL-THERM® PRO

Closed Cell Spray Foam

# PROVEN NEXT-GEN PERFORMANCE



Our new Natural-Therm® Pro spray foam insulation delivers greater flexibility with testing for more applications and the ability to spray at lower temperature settings.

## KEY FEATURES

- Built on the consistent, applicator friendly, low-VOC<sup>1</sup> backbone of Natural-Therm® 2.0 HFO.
- Optimized for improved reactivity in the spring/fall transition seasons
- Tested for new commercial credentials, making it the go-to choice for specifiers and sprayers alike.
- Backed by an industry-leading team of field technicians and building science experts that are ready to support your most complex residential and commercial projects.

	NATURAL-THERM® 2.0 HFO	NATURAL-THERM® PRO
<b>Key Feature</b>		
<b>R-Value</b> <i>(@ 1 inch)</i>	> 7	> 7
<b>Yield</b> <i>(board feet per set)</i>	4,500–5,000+	4,500–5,000+
<b>UL GreenGuard Gold</b>	Certified	Certified
<b>Fire Assemblies for Interior / Exterior Walls</b>	Limited Assemblies	Extensive Assemblies
<b>C1029</b> <i>Commercial Standard</i>	—	✓
<b>Air &amp; Water Barrier</b> <i>Assemblies for Exterior Walls</i>	—	✓
<b>Operating Window</b>	—	Wider Processing Window
<b>Adhesion to Substrate</b>	—	Improved on Concrete / Metal
<b>Proportioner Settings</b>	—	Allows for Lower Processing Temps

<sup>1</sup>www.ul.com/gg