



PRO PINK[®] COMFORTSEAL[™] SILL GASKET

Owens Corning[®] ProPink ComfortSeal[™] Sill Gasket is a polyethylene foam gasket, which provides resilient sealing in new and retrofit construction.



Features

- Compressible closed-cell polyethylene foam gasket
- Long-lasting and durable
- Cost-effective
- Installs and cuts easily
- Reduces air infiltration and heat loss
- Reduces noise transmission
- Insect resistant
- Moisture resistant

Physical Properties

	PROPERTY	TEST METHOD	VALUE
PHYSICAL	Vertical compressive strength (psi)	ASTM D3575-08	
	Compressive strength	Suffix D @ 25%/50%	2.7/10.4
	Compression set (%)	ASTM D3575-08 Suffix B	29.4
	Tear resistance (lb/ft ²)	ASTM D3575-08 Suffix T MD/CMD	8.3/11.5
	Density (lb/ft ³)	ASTM D3575-08	1.2
MOISTURE	Water absorption (lb/ft ²)	ASTM D3575-08 Suffix L	< 0.1 / sq ft / 24 hours
	Water vapor transmission rate	ASTM F-1249	
	GM/100 in ² /24 hours	Method 3005 FED STD 101	0.089
THERMAL	Thermal resistance R-Value @ initial thickness (hr-ft ² -0F/BTU)	ASTM C518-91	0.68

1. R means resistance to heat flow; the higher the value, the greater the insulation power. Value given is for initial thickness. Value after installation/compression will be lower.

Standards, Code Compliance

- Class A Fire Rating
- Does not support mold growth
- GreenGuard™ Certified

Applications

- Provides a seal against air leakage, moisture, and insect intrusion at the juncture of the foundation wall and sill plate.
- Expansion joint material for poured concrete and concrete block slab and wall construction.

Installation Instructions

- Smooth the top surface of the foundation wall for minimal variation.
- Unroll the sill gasket on the top surface of the foundation wall or fasten to the bottom of the sill plate on tilt-up wall sections with ridged side toward roughest surface.
- Overlap all end and perpendicular joints.
- Pierce the sill gasket at anchor bolt locations.
- Set and anchor sill plate to the foundation wall.

Caution: ProPink ComfortSeal™ Sill Gasket is combustible and will ignite. The product may contain flammable vapors and should be stored in well-ventilated areas. Do not expose the product to open flame during shipping, storage, installation, or use.

Recommended tools

- Safety glasses
- Cut-resistant gloves
- Ladder
- Construction or hammer stapler
- 5/16 inch heavy-duty staples
- Scissors or utility knife

Storage Recommendations

- Store product in packaging away from heat sources
- Do not store in the sun

Dimensions

MATERIAL	COLOR	LENGTH	PRODUCT SIZE
Polyethylene Foam	Pink	50 ft rolls	3½", 5½", 7½" widths x 3/16" thick
Polyethylene Foam	Black	50 ft rolls	3½", 5½", 7½" widths x 3/16" thick

Environmental and Sustainability

Owens Corning is a world leader in building material systems, insulation, and composite solutions, delivering a broad range of high-quality products and services.

Owens Corning is committed to driving sustainability by delivering solutions, transforming markets, and enhancing lives. More information can be found at www.owenscorning.com.

Certifications and Sustainable Features

- GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg



Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein.



OWENS CORNING INSULATING SYSTEMS, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OH 43659 USA
1-800-GET-PINK®
www.owenscorning.com