



SELECTSOUND® BLACK ACOUSTIC BLANKET

SelectSound® Black Acoustic Blanket are made of inorganic glass fibers with a thermosetting resin binder and formed into flexible blanket that is dimensionally stable and will not shrink or warp.

SelectSound® Black Acoustic Blanket comes with a smooth black veil surface over a gray/black blanket that provides low light reflectivity. The veil additionally aids in resisting damage during installation and service. When necessary, the durable black veil facing may be cleaned by light vacuuming.

Features

SelectSound® Black Acoustic Blankets provides excellent acoustical performance for multiplex theaters, sound studios and performing arts centers.

Standards, Codes Compliance

- ASTM C553, Mineral Fiber Thermal Insulation: Types I and II
- UL 181 Air Erosion
- NFPA 90A and 90B Compliant
- ICC Compliant
- California Title 24

Physical Properties

PROPERTY	VALUE	TEST METHOD
Density	1.5 pcf	ASTM C303
Water Vapour Sorption	<5% by weight at 49°C (120°F), 95% R.H.	ASTM C1104
Fungi Resistance	Meets requirements	C1338
Corrosion to Copper, and Aluminum	Pass - both metals	ASTM C665
Corrosion to Steel	Pass	ASTM C1617
Thermal Conductivity at 24°C (75°F) mean	0.035 W/m·°C (0.24 Btu·in/hr·ft²·°F)	ASTM C518
Air Erosion	Rated at 5.1 m/sec (3,000 fpm)	UL 181
Surface Burning Characteristics¹	Flame Spread Index 25, Smoke Developed Index 50	UL 723; ASTM E84; or CAN/ULC-S102

¹ The surface burning characteristics of these products have been determined in accordance with UL 723, ASTM E84 or CAN/ULC-S102. Values are reported to the nearest 5 rating.

Acoustical Performance

ASTM C423; Mounting Type A; - Material placed against solid backing.

THICKNESS		OCTAVE BAND CENTER FREQUENCIES, HZ						
MM	IN.	125	250	500	1000	2000	4000	NRC
25	1	0.12	0.35	0.76	0.97	1.00	1.00	0.75
51	2	0.16	0.61	0.94	1.04	0.95	0.99	0.90

Availability

SelectSound® Black Acoustic Blanket is available in:

- 25 mm x 1219 mm x 30 m (1" x 48" x 100') rolls
- 51 mm x 1219 mm x 15 m (2" x 48" x 50') rolls

Installation Instructions

Lightweight and resilient, SelectSound® Black Acoustic Blankets are easy to handle, fabricate and install. Both stick pins and adhesives can be used to secure boards to drywall, concrete block or precast concrete. See SelectSound® Board and Blanket Recommended Installation Instructions; Pub. No. 10024403

Design Considerations

Acoustical performance of interior surfaces can generally be improved by increasing acoustical material thickness. SelectSound® Black Acoustic Blanket can be specified for use in conjunction with other Owens Corning acoustical materials to provide additional performance.

Owens Corning also manufactures SelectSound® Black Acoustic Board. This rigid rectangular product is ideal for use behind fabric on theater walls, in sound studios and performing arts centers.

Certifications and Sustainable Features

- Certified by SCS Global Services to contain an average 53% with minimum 22% post-consumer and balance 31% pre-consumer recycled glass content



Environmental and Sustainability

Owens Corning is a worldwide leader in building material systems, insulation, and composite solutions, delivering a broad range of high-quality products and services.

Owens Corning is committed to driving sustainability by delivering solutions, transforming markets, and enhancing lives. More information can be found at www.owenscorning.ca or www.owenscorninglibrary.ca.

Technical Services Available

For Canadian Technical inquiries, please contact our technical team at www.owenscorning.ca/contacttech.

Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein. SCS Global Services provides independent verification of recycled content in building materials and verifies recycled content claims made by manufacturers.

For more information, visit www.SCSglobalservices.com.

Notes

For additional information, refer to the Safe Use Instruction Sheet (SUIS) found in the SDS Database via <http://sds.owenscorning.com>.

OWENS CORNING INSULATING SYSTEMS, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OHIO, USA 43659
1-800-GET-PINK®
www.owenscorning.ca