

PROPINK COMFORTSEAL™
GASKET (SHOWN DARK PINK)
AT WALL TOP PLATE

JOINTSEALER® FOAM JOINT
TAPE (SHOWN ORANGE)

- 3 1/2" (89mm) BRICK VENEER
- 1" (25mm) AIRSPACE
- 0.8" to 2" (20 to 51mm)
FOAMULAR® NGX™ CODEBORD® SHEATHING:
R4 to R10 (RSI 0.70 to 1.76)
- PINK NEXT GEN™ FIBERGLAS® INSULATION
R19/R22/R24 (RSI 3.34/3.87/4.23)

JOINTSEALER® FOAM JOINT
TAPE (SHOWN ORANGE)

PROPINK COMFORTSEAL™
GASKET (SHOWN DARK PINK)

FLASHING BEHIND SEALING
GASKET (SHOWN DASHED)

PROPINK COMFORTSEAL™
GASKET (SHOWN DARK PINK)
BELOW SILL PLATE

DAMP-PROOFING & WATER-PROOFING
TO FOUNDATION WALL BELOW GRADE

FOUNDATION DRAINAGE LAYER

CONCRETE FOUNDATION WALL
(THICKNESS VARIES)

PROPINK® FIBERGLAS® BLOWN
INSULATION: R40-R60 (RSI 7.04-10.57)

6 MIL. POLY VAPOUR/ AIR
BARRIER (SHOWN DASHED)

SEAL CEILING 6 MIL. POLY
AIR/VAPOUR BARRIER TO UPPER
TOP PLATE WITH ACOUSTIC
SEALANT (SHOWN RED)

2x6 (38x140mm) STUD WALL

6 MIL. POLY VAPOUR
BARRIER (SHOWN DASHED)

GYPSUM BOARD

PINK NEXT GEN™ FIBERGLAS®
INSULATION: R20/R22/R24
(RSI 3.52/3.87/4.23) w/6 MIL. POLY
VAPOUR BARRIER (SHOWN DASHED)

FLOOR JOISTS

2x6 (38x140mm) STUD WALL

GYPSUM BOARD

6 MIL. POLY VAPOUR
BARRIER (SHOWN DASHED)

FLOOR JOISTS

PINK NEXT GEN™ FIBERGLAS®
INSULATION: R20/R22/R24
(RSI 3.52/3.87/4.23) w/6 MIL. POLY
VAPOUR BARRIER (SHOWN DASHED)

1" (25mm) FOAMULAR® NGX™
CODEBORD® R5 (RSI 0.88)

2x4 (38x89mm) WOOD STUDS

PINK NEXT GEN™ FIBERGLAS®

INSULATION: R12/R14 (RSI 2.11/2.46)

6 MIL. POLY VAPOUR BARRIER

(SHOWN DASHED)

GYPSUM BOARD

CONCRETE FLOOR SLAB

1" (25mm) FOAMULAR® NGX™

CODEBORD®: R5 (RSI 0.88) WITH

TAPED JOINTS (OPTIONAL 6 MIL.

POLY VAPOUR/AIR BARRIER

GRANULAR BASE