



PROPINK COMPLETE™ FABRIC

Product Attributes

Durability

PROPINK Complete™ Fabric is designed to provide minimal stretch and to resist tearing during the installation process.

Performance

The unique structure of PROPIK Complete™ Fabric allows air to pass through, but not glass fibers, during the installation process.

Translucent

PROPIK Complete™ Fabric is translucent so framing members are clearly visible for easy application. It also allows a convenient visual check when installing PROPIK Complete™ insulation.

Dimensions

PROPIK Complete™ Fabric is available in rolls measuring 8, 9, and 10 feet wide by 600 feet long.

Handling

The sheets are folded and shipped in easy-to-handle rolls, 4–5 feet wide by 14 inches in diameter, weighing 30–38 pounds each.

Design Considerations

Owens Corning does not recommend using PROPIK Complete™ Fabric with glass fiber loosefill insulation other than Owens Corning products.

Owens Corning will not accept liability when the product is not installed according to instructions.

The perm rating for PROPIK Complete™ Fabric is well above 5 and, therefore, will not act as a water vapor retarder when applied to wall and ceiling assemblies.

For complete installation instructions, please reference publication 101133.

Product Data

- As tested in accordance with ASTM C1338, PROPIK Complete™ Fabric exhibited no mold growth.
- The surface burning characteristics of this product have been determined in accordance with ASTM E84¹.

| | |
|------------------|---|
| *Flame Spread | 0 |
| *Smoke Developed | 5 |

¹ This standard is used to measure and describe the response of materials, products, or assemblies to heat and flame under controlled conditions, but does not by itself incorporate all the factors required for fire hazard or fire risk assessment of the materials, products, or assemblies under actual fire conditions. However, the results of these tests may be used as elements of a fire risk assessment that takes into account all of the factors pertinent to an assessment of the fire hazard of a particular end use. Values are reported to the nearest five (5) rating.

PROPIK Complete™ Fabric meets ASTM E84 Flame Spread and Smoke Developed rating required to be left exposed, allowing for extended periods of exposure. The fabric, however, is not designed to be left exposed permanently.

Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for, the accuracy or reliability of data associated with particular uses of any product described herein. SCS Global Services provides independent verification of recycled content in building materials and verifies recycled content claims made by manufacturers. For more information, visit www.SCSglobalservices.com.

Notes

For additional information, refer to the Safe Use Instruction Sheet (SUIS) found in the SDS Database via <http://sds.owenscorning.com>.

OWENS CORNING INSULATING SYSTEMS, LLC

ONE OWENS CORNING PARKWAY
TOLEDO, OH 43659 USA

1-800-327-6162
www.owenscorning.com

Pub. No. 59126-G. Printed in U.S.A. February 2022. The color PINK is a registered trademark of Owens Corning. © 2021 Owens Corning. All Rights Reserved.